
# **PHP7036DT** GE Profile<sup>™</sup> 36" Built-In Touch-Control Induction Cooktop

## DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**IMPORTANT:** Requires a 3" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.


**NOTE:** 36" induction cooktops are approved for use over select GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered.


Before installing, consult installation instructions packed with product for current dimensional data.



To insure accuracy, it is best to make a template when cutting the opening in the counter

### INSTALLATION ABOVE A WALL OVEN





13" MAX. depth of unprotected

30" MIN. Clearance from

countertop to unprotected

overhead surface

2" MIN. clearance

to side wall from cut-out on the left of the unit

See label next

to rear wall

to nameplate for MIN, clearance

overhead cabinets

**NOTE:** Check local codes for required breaker size.





For answers to your Monogram, GE Café<sup>™</sup>, GE Profile<sup>™</sup> or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center<sup>®</sup> Service, 800.626.2000.

reaker size.

2" MIN. Clearance

below the 15" MIN.

clearance height.

15" MIN. height

from countertop

on both sides of

cooktop

to nearest cabinet (including light rails)

from cutout to nearest

vertical wall or cabinet

on right side of the unit




## PHP7036DT

GE Profile<sup>™</sup> 36" Built-In Touch-Control Induction Cooktop

## FEATURES AND BENEFITS

Maximum Responsiveness - 11 Control Levels Power Boil Precision Temperature Control Guided Cooking Easy Clean Surface Safe Surface Most Efficient Heating Synchronized Elements Chef Connect Compatible Cooktop with Smart Timer Built-in WiFi Control Lock Fit Guarantee Model PHP7036DTBB - Black on black



#### COMPATIBLE COOKTOP WITH SMART COOKWARE

Smart pans easily pair with this smart cooktop to ensure you get the perfect cooking results. Accessories sold separately.

### **OPTIONAL SOUS VIDE PROBE**

A Sous Vide Probe lets you achieve great results on the stove. Order part number JXPROBE1.

### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications.

Visit geappliances.com for more info.

