



on flexibility • precise air™ convection system • 2003 built-in reference guide • eight-pass bake element • sculptured handles

# GE Profile™ and GE® Built-In Cooking Products

Product dimensions and installation information.

imagination at work



# Table of Contents

---

**Before You Start** . . . . . 3

**Wall Ovens** . . . . . 4 - 14

    30" Electric Double Ovens . . . . . 5

    27" Electric Double Ovens . . . . . 6

    24" Electric Double Ovens . . . . . 7

    27" and 30" Microwave Double Ovens . . . . . 8 - 9

    30" Electric Single Ovens . . . . . 10 - 11

    27" and 24" Electric Single Ovens . . . . . 12 - 13

    24" Gas Single Ovens . . . . . 14

**Warming Drawers** . . . . . 15

**Cooktops** . . . . . 16 - 23

    36", 30" and 21" Electric Cooktops . . . . . 17 - 18

    36" and 30" Gas Cooktops . . . . . 19

    Downdraft Electric and Gas Cooktops . . . . . 20 - 21

    Modular Downdraft Cooktops . . . . . 22 - 23

**Slide-In and Drop-In Ranges** . . . . . 24 - 29

    30" Electric Slide-In Ranges . . . . . 25 - 26

    30" Gas and Dual-Fuel Slide-In Ranges . . . . . 27

    30" Electric Drop-In Ranges . . . . . 28

    27" Electric Drop-In Ranges . . . . . 29

**Ventilation Options** . . . . . 30 - 34

    Designer Hoods . . . . . 31

    Slide-Out Hoods . . . . . 31

    Hoods . . . . . 32

    Telescopic Downdraft Systems . . . . . 33 - 34

# Before You Start

---

Dimensions and information shown are for **planning purposes only** and subject to change without notice. See Installation Instructions, packed with product, for current dimensional data before making cutouts.

Proper installation is your responsibility. Make sure you have everything necessary for correct installation. It is the responsibility of the installer to comply with the clearances specified.

See Installation Instructions packed with product before installing product. Installation instructions contain important safety information, accurate dimensions, plumbing/electrical/gas requirements, and detailed instructions necessary for proper installation.

*Any alteration* to the product or installation of the product that is not approved by GE can/will void the product U.L. or A.G.A. approval and GE **will not** be responsible for any resulting liability. Furthermore, such alteration to the product or installation will, at the discretion of GE, void the product warranty.

**Important: Observe all governing codes and ordinances.**

**Note:** All dimensions shown are in inches.

## QuickSpecs—1-800-432-3729

This automated fax-on-demand system provides a quick reference to installation dimensions for GE Monogram®, GE Profile Performance™, GE Profile™, GE® and Hotpoint appliances:

- ***No fax request forms!*** The QuickSpecs system is a touchtone phone activated system. Simply follow the voice prompts and make your selection from any touchtone telephone.
- ***Model specific installation dimensions.*** You can now obtain accurate installation dimensions by individual model numbers for virtually every model. Make your selection from the List of Available Documents (available by fax through QuickSpecs). You may select up to 15 model documents per phone call.
- ***Fax information to any fax telephone number.*** Once you make your selection, you will be asked to enter the fax telephone number where you wish your request to be faxed (your office, job site, customer). It will be faxed to the specified fax number immediately.
- ***Available 24 hours a day, 7 days a week.***

# Built-In Wall Ovens



## For All Installations

The oven may be supported by either a solid bottom or two runners. The solid bottom or two runners should be level with the bottom edge of the cutout opening. The entire weight of the oven is supported by the bottom runners. Be sure oven support is solid enough to hold the designated pounds. Also, be sure the oven support is level and straight. There is no way to level the oven after installation.

**Note:** Always remove oven door before installing product.

## Electrical & Gas Information

Electrical ground is required for all models. Grounded electrical outlet is required for gas models. Proper gas supply is required for gas models. Check with your local utilities for electrical codes that apply in your area.

## Installation Information

Cabinet space must be provided to enclose the recessed part of the oven. It is best to make a template to ensure accurate cutting. Be sure oven is securely installed to a cabinet that is firmly attached to the house structure. Weight of the oven door could potentially cause the oven to tip and result in injury.


## Undercounter Installation

**Do not install any oven in a base cabinet with a countertop or cooktop above it unless it has been rated for undercounter installation. Check Installation Instructions and approval label on product.**


**Note:** Cooktop must be approved for use over oven.

# Built-In Double Ovens: 30" Electric

## Models JT955, JT952, JTP48 and JTP28 Dimensions (in inches)



MOST 30" WALL CABINETS CAN BE USED WITH THIS UNIT.  
THE OPENING BETWEEN THE INSIDE WALLS MUST BE AT LEAST 28-1/2" WIDE.



| Cabinet   | 30"           |
|---|---------------|
| A – Overlap of Oven Over Side Edges of Cutout   | 11/16" – 3/4" |
| B – Overlap of Oven at Top and Bottom of Cutout | 1"            |
| Oven  |               |
| C – Overall Depth                               | 23-1/2"       |
| D – Overall Height                              | 52-7/8"       |
| E – Overall Width                               | 29-3/4"       |


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.



### Models JK955, JKP48 and JKP28 Dimensions (in inches)





| <b>Cabinet</b>                                     |                       | <b>27"</b>              |
|--|-----------------------|-------------------------|
| A – Cabinet Width Required                         |                       | 27" min.                |
| B – Minimum Cabinet Depth                          |                       | 23-5/8"                 |
| C – Minimum Opening Width                          |                       | 25" min. – 25-1/4" max. |
| D – Opening Height                                 |                       | 50-1/8" max.            |
| E – Recommended Minimum Cutout Location from Floor |                       | 13-1/4"                 |
| <b>Oven</b>  |                       |                         |
| F – Overall Depth                                  |                       | 23-5/8"                 |
| G – Overall Height                                 | w/o trim<br>with trim | 50-1/4"<br>51"          |
| H – Overall Width                                  |                       | 26-5/8"                 |

**Note:** If marks, blemishes or the cutout opening is visible above the installed oven, it may be necessary to add wood shims under the runners and front trim until the marks or openings are covered.

Listed by  
Underwriters  
Laboratories

# Built-In Double Ovens: 24" Electric

## Model JRP24 Dimensions (in inches)



| Cabinet  |           | 24"          |
|--|-----------|--------------|
| A – Cabinet Width Required                         |           | 24" min.     |
| B – Minimum Cabinet Depth                          |           | 23-1/2"      |
| C – Minimum Opening Width                          |           | 22-1/2"      |
| D – Opening Height                                 |           | 48-1/8" min. |
| E – Recommended Minimum Cutout Location from Floor |           | 14"          |
| Oven   |           |              |
| F – Overall Depth                                  |           | 23-1/8"      |
| G – Overall Height                                 | w/o trim  | 48-1/8"      |
|  | with trim | 49-1/4"      |
| H – Overall Width                                  |           | 23-3/4"      |


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

**Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.**

# Built-In Microwave Combination Ovens: 30" Electric

## Models JT965 and JTP86 Dimensions (in inches)




MOST 30" WALL CABINETS CAN BE USED WITH THIS UNIT.  
THE OPENING BETWEEN THE INSIDE WALLS MUST BE AT LEAST 28-1/2" WIDE.

| Cabinet                                       | 30"     |
|---|---------|
| A – Overlap of Oven Over Side Edges of Cutout | 11/16"  |
| B – Overlap of Oven at Bottom of Cutout       | 1"      |
| C – Overlap of Oven at Top of Cutout          | 1/2"    |
| Oven  |         |
| D – Overall Depth                             | 23-1/2" |
| E – Overall Height                            | 43-1/2" |
| F – Overall Width                             | 29-3/4" |

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.





Listed by  
Underwriters  
Laboratories





# Built-In Microwave Double Ovens: 27" Electric

## Model JKP86 Dimensions (in inches)



| Cabinet                                |           | 27"                     |
|--|-----------|-------------------------|
| A – Cabinet Width Required             |           | 27" min.                |
| B – Minimum Cabinet Depth              |           | 23-5/8"                 |
| C – Minimum Opening Width              |           | 25" min. – 25-1/4" max. |
| D – Opening Height                     |           | 41-1/4" max.            |
| E – Minimum Cutout Location from Floor |           | 22"                     |
| Oven                                   |           |                         |
| F – Overall Depth                      |           | 23-5/8"                 |
| G – Overall Height                     | w/o trim  | 41-3/8"                 |
|  | with trim | 42-1/8"                 |
| H – Overall Width                      |           | 26-5/8"                 |

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** If marks, blemishes or the cutout opening is visible above the installed oven, it may be necessary to add wood shims under the runners and front trim until the marks or openings are covered.




Listed by  
Underwriters  
Laboratories

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.

# Built-In Single Ovens: 30" Electric

## Models JT915, JT912 and JTP20 Dimensions (in inches)

### Single Oven Wall-Mount or Cabinet Installation (in inches)




Allow minimum of 21" for clearance to adjacent corners, drawers, walls, or etc.

A=Allow 1" overlap of oven over top and bottom edges of cutout.

B=Allow 11/16"-3/4" for overlap of oven over side edges of cutout.

### Recommended for solid bottom installation



(Must support 275 Lbs.)

Most 30" Wall Cabinets can be used with this unit.

**Note:** These ovens are *not* approved for stackable or side-by-side installations.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.




Listed by  
Underwriters  
Laboratories




# Built-In Single Ovens—Undercounter Installation: 30" Electric

## Models JT915, JT912 and JTP20 Dimensions (in inches)




**Notes:** 36" Ribbon cooktops (excluding JP960) are approved for use over GE 30" Single Wall Ovens and warming drawers. 30" Ribbon cooktops are approved for use over GE 30" and 27" Single Wall Ovens and warming drawers. Refer to cooktop and wall oven installation instructions packed with product for current dimensional data.

### Optional Undercounter Installation With 36" Gas Cooktop (in inches)



**Note:** For standard or sealed burner cooktop installation information over the 30" wall oven, refer to 27" wall oven installation, page 12.

### Optional Undercounter Installation With 30" CleanDesign or Sealed Burner Gas Cooktop (in inches)



This installation is to achieve minimum gap between bottom of countertop and control panel.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

**Note:** For this installation, the bottom trim **will not** be flush with a typical 4" toe kick.


**Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.**




Listed by  
Underwriters  
Laboratories

# Built-In Single Ovens: 27" Electric

## Models JK915, JKP20 and JKS06 Dimensions (in inches)




## Sealed Burner Gas Cooktop Installation



**Note:** Do not install any oven in a base cabinet with a countertop or cooktop above it unless it has been rated for undercounter installation. Check Installation Instructions and approved label on product.


## Standard Burner Gas Cooktop Installation



**Note:** See cooktop installation instructions for cutout size. See label on back of oven for approved cooktop models.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.



**Note:** 36" ribbon cooktops (excluding JP960) are approved for use over GE 30" single wall ovens and warming drawers. 30" ribbon cooktops are approved for use over GE 30" and GE 27" single wall ovens and warming drawers. Refer to cooktop and wall oven installation information packed with products for current dimensional data.



Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.



Listed by Underwriters Laboratories

# Built-In Single Ovens: 24" Electric

## Models JRP15 and JRS04 Dimensions (in inches)



(Must support 275 Lbs.)

| Cabinet                    |           | 24"      |
|----------------------------|-----------|----------|
| A – Cabinet Width Required |           | 24" min. |
| B – Minimum Cabinet Depth  |           | 23-1/2"  |
| C – Minimum Opening Width  |           | 22-1/2"  |
| Oven                       |           |          |
| D – Overall Depth          |           | 23-1/8"  |
| E – Overall Height         | w/o trim  | 27-1/2"  |
|                            | with trim | 28-3/16" |
| F – Overall Width          |           | 23-3/4"  |

**Note:** Models JRP15 and JRS04 are not approved for stackable or side-by-side installations.


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.



### Models JGRP17 and JGRS14 Dimensions (in inches)




**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.






# Built-In 30" and 27" Warming Drawers


## Models JTD915 and JKD915 Dimensions (in inches)



### Under Oven Installation (in inches)



### Undercounter Installation (in inches)



**Installation Information:** Before installing, consult installation instructions packed with product for current dimensional data.



# Built-In Cooktops



## Electrical & Gas Information

Electrical ground is required for electric models. Grounded electrical outlet is required for gas models. Proper gas supply is required for gas models. Check with your local utilities for electrical codes that apply in your area.

## Installation Information

*All gas cooktop models* require a 7/16" free area below cooktop height to combustable material. 0" clearance is required between left and right sides of cooktop below countertop. AGA requires 18" minimum from cooktop to adjacent overhead cabinets.

*All electric cooktop models* require a 5" free area between the bottom of the cooktop to any combustable material, i.e. shelving. Free area not required when installing wall oven underneath cooktop. Requires an 18" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.


## Installation with Undercounter Wall Oven

A built-in oven may be installed under cooktop if approved for this type of installation. Refer to oven manufacturer's Installation Instructions for approval and proper dimensions.

# Built-In Cooktops: 36" and 30" Electric CleanDesign

## Models JP969, JP961, JP960, JP939, JP931, JP930, JP350 and JP340 Dimensions (in inches)

### Counter Installation Dimensions (in inches)



### Filler Trim Kit


When replacing an old GE 30" cooktop (with larger opening) with Models JP939/930/350/340, use the following one-piece trim kit to fill in the over-size hole. Available at additional cost.

JXTR31W (True White)

JXTR31C (True Bisque)

JXTR31B (Black—use with black glass cooktops with a white, bisque or black pattern)

### Cooktop Dimensions (in inches)



### Built-in CleanDesign Cooktops:

Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires an 18" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

36" Ribbon cooktops (excluding JP960) are approved for use over GE 30" Single Wall Ovens and warming drawers. 30" Ribbon cooktops are approved for use over GE 30" and 27" Single Wall Ovens and warming drawers. Refer to cooktop and wall oven installation instructions packed with product for current dimensional data.

**Notes:** If installing with a GE Profile™ Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft.

Consult cabinet and countertop manufacturer's specs for flush mount installation prior to install.

The countertop must be at least 26" deep with a flat surface area of 23-1/2" or more, front to back. JP939S, JGP930S, JP350S and JGP932S require 23-5/8" flat surface area. In addition, other clearances to the front edge of the countertop must be considered.

### Optional Accessory

ZX375GRD Universal Griddle is non-stick and fits all electric smooth top ranges, cooktops, electric bridge elements and gas ranges.

### Flush Mount Installation Kit

Accommodates both 36" and 30" installations.

Not for use with stainless steel models.

JXFLMTW (True White)

JXFLMCC (True Bisque)

JXFLMBB (Black—use with black glass cooktops with a white, bisque or black pattern)

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

### Cooktop Dimensions (in inches)

| Model            | Overall |        |        | Cutout |        |       | To Edge of Front Counter (Min.) |
|------------------|---------|--------|--------|--------|--------|-------|---------------------------------|
|                  | W       | D      | A      | E      | F      | G     |                                 |
| JP969WH/CH/BH    | 36      | 20-3/8 | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP961TH/KH/BH    | 36      | 20-3/8 | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP960TC/KC/BC    | 36      | 20-3/8 | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP939WH/CH/BH    | 29-3/4  | 20-7/8 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP931TH/KH/BH    | 29-3/4  | 20-7/8 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP930TC/KC/BC    | 29-3/4  | 20-7/8 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP350TC/WC/KC/BC | 29-3/4  | 20-7/8 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP340WC/CC/BC    | 29-3/4  | 20-7/8 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |

\*Depth of unit at conduit connection location (rear) is 6-1/4" on models JP969/939 and 4-5/8" on models JP961/960/931/930/350/340.

### Stainless Steel Cooktop Dimensions (in inches)


| Model   | Overall |        |        | Cutout |        |       | To Edge of Front Counter (Min.) |
|---------|---------|--------|--------|--------|--------|-------|---------------------------------|
|         | W       | D      | A      | E      | F      | G     |                                 |
| JP969SH | 36-1/8  | 21     | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP961SH | 36-1/8  | 21     | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP960SC | 36-1/8  | 21     | 3-1/4* | 33-7/8 | 19-1/8 | 2-1/2 |                                 |
| JP939SH | 29-7/8  | 21-1/2 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP931SH | 29-7/8  | 21-1/2 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP930SC | 29-7/8  | 21-1/2 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |
| JP350SC | 29-7/8  | 21-1/2 | 3-1/4* | 28-1/2 | 19-5/8 | 2-1/2 |                                 |

\*Depth of unit at conduit connection location (rear) is 6-1/4" on models JP969/939 and 4-5/8" on models JP961/960/931/930/350.

# Built-In Cooktops: 36", 30" and 21" Electric Coil

## Models JP626, JP328, JP202 and JP201 Dimensions (in inches)

### Counter Installation Dimensions (in inches)



### Built-In Electric Cooktops

Required free area between the bottom of the cooktop and any combustible material, i.e., shelving is 5" minimum on models JP626/328 and 1-1/2" minimum on models JP201/202. Free area not required when installing wall oven underneath. Requires an 18" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

Cooktop model JP328 is approved for use over select GE 30" or 27" Single Wall Ovens. JP626 is approved for use over GE 30" Single Wall Ovens only. Refer to cooktop and wall oven installation instructions packed with product for current dimensional data.


Cooktop models JP201CB and JP202D are approved for use over GE undersink dishwasher model GSM2100. Refer to cooktop installation instructions packed with product for current dimensional data.

**Notes:** If installing with a GE Profile Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft.  
The countertop must be at least 26" deep with a flat surface area of 23-1/2" or more, front to back. In addition, other clearances to the front edge of the countertop must be considered.

**Filler Trim Kit**—When replacing an old GE 30" cooktop (with larger opening) with Model JP328 use the following one-piece trim kit to fill in the over-size hole. Available at additional cost.  
JXTR31W (White)  
JXTR31C (Bisque)  
JXTR31B (Black)

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

### Built-In Cooktop Dimensions (in inches)




### Dimensions (in inches)

| Model | Overall |        | Cutout |        | Minimum Spacing To Nearest Combustible Wall |       |       | To Edge of Front Counter (Min.) |
|-------|---------|--------|--------|--------|---|-------|-------|---------------------------------|
|       | W       | D      | A      | B      | C   | R     | L     | F                               |
| JP626 | 35-1/2  | 21     | 33-7/8 | 19-1/8 | 2-1/2                                       | 3-3/4 | 3-3/4 | 2-1/2                           |
| JP328 | 30-1/4  | 21-1/4 | 28-1/2 | 19-1/2 | 1-3/4                                       | 2     | 5-1/2 | 2-1/2                           |
| JP202 | 21-1/4  | 16-5/8 | 20-1/8 | 16-1/8 | 2   | 2     | 2     | 2-3/4                           |
| JP201 | 21-1/4  | 16-5/8 | 20-1/8 | 16-1/8 | 2   | 2     | 2     | 2-3/4                           |


# Built-In Cooktops: 36 " and 30" Gas

## Models JGP963, JGP962, JGP960, JGP636, JGP628, JGP933, JGP932, JGP930, JGP336, JGP328 and JGP320 Dimensions (in inches)

### Counter Installation Dimensions (in inches)



### Cooktop Dimensions (in inches)



**Note:** All gas cooktop models require 7/16" free area below cooktop height to combustible material. 0" clearance is required between left and right sides of cooktop below countertop. Requires 18" minimum from countertop to adjacent overhead cabinets.\* \*AGA requirement.

**Note:** If installing with a GE Profile™ Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft.

### Installation With Single Wall Oven Information:

30" Gas Cooktops are approved for use over GE 27" Wall Ovens. 36" and 30" Gas Cooktops are approved for use over 30" Wall Ovens. Refer to cooktop and wall oven installation instructions packed with product for current dimensional data.

### Optional Gas Range Wok Accessory

(Available at additional cost)

JXWK = Wok accessory holder sits on top of maximum burner grate to hold a **round-bottom** wok. For use with JGP960/930/636/336 models only.

JXWK2 = Wok accessory holder sits on top of maximum burner grate to hold a **round-bottom** wok. For use with JGP963/933/962/932 models only.


**Note:** Electrical cable is not supplied with unit.

### Dimensions (in inches)


| Model  | Overall |         |        | Cutout |        | Minimum Spacing To Nearest Combustible Wall |       |       | To Edge of Front Counter |
|--------|---------|---------|--------|--------|--------|---|-------|-------|--------------------------|
|        | W       | D       | H      | A      | B      | C   | L     | R     | F                        |
| JGP963 | 36      | 21      | 3-3/16 | 33-7/8 | 19-1/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP933 | 30      | 21      | 3-3/16 | 28-1/2 | 19-5/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP962 | 36      | 20-7/16 | 3-1/16 | 33-7/8 | 19-1/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP932 | 29-3/4  | 21      | 3-3/16 | 28-1/2 | 19-5/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP960 | 36      | 21      | 3-1/16 | 33-7/8 | 19-1/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP636 | 36      | 21      | 3-1/16 | 33-7/8 | 19-1/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP628 | 36      | 21      | 3-3/16 | 33-7/8 | 19-1/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP930 | 30      | 21      | 2-1/2  | 28-1/2 | 19-5/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP336 | 30      | 21      | 2-1/2  | 28-1/2 | 19-5/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP328 | 30      | 21      | 3-3/16 | 28-1/2 | 19-5/8 | 2-1/4                                       | 3-3/4 | 3-3/4 | 2-1/2                    |
| JGP320 | 30-1/4  | 21-1/4  | 3-9/32 | 28-1/2 | 19-5/8 | 1-3/4                                       | 3     | 3     | 3-1/4                    |

\*Allow 5-3/4" depth at rear for electrical and gas connections.

### Gas Connection Models JGP963/962/636/628



### Gas Connection Models JGP933/932/336/328/320




**Important:** Before installing, consult installation instructions packed with product for current dimensional data.



# Built-In Cooktops: 30" Electric Downdraft

## Model JP989 Dimensions (in inches)

### Built-In Downdraft Cooktops Dimensions (in inches)



#### Wall Installation

Wall installations require 25" countertop depth. When cabinet is flush against the wall, the fan housing can be rotated to the horizontal position for direct venting through rear wall. Make a countertop cutout in the range cabinet according to unit dimensions and installation type. Duct hole is positioned in back of cabinet for through-the-wall ducting.

#### Peninsula or Island Installation

For peninsula/islands a minimum 26" countertop depth is suggested. Blower should be in vertical position. Island or peninsula cabinets may require adjustment in cutout depth and/or location within the width dimensions. Duct hole is positioned in bottom of cabinet for island or peninsula installation.

#### Slab Installation


For peninsula or island installation and rear wall ducting, **6" PVC duct or locally approved piping should be used if installing under a poured concrete slab.**

**Note:** Electrical cable is not supplied with unit.

**JXCK89 Electrical Connection Kit.** Optional accessory kit for JP989 electric downdraft cooktop only, includes junction box and conduit.


### Cutout Dimensions (in inches)

**Note:** These cooktops are approved for indoor use only.



**Note:** A 5" minimum spacing to adjacent side wall is required on JGP989. A 6" minimum spacing to adjacent side wall is required on JP989.


### Cabinet Dimensions (in inches)




#### Receptacle Location

Install an approved junction box within shaded area shown in diagram. Junction box must be at least 10-1/2" below top of cabinet.


### Venting Options




Inside Wall Through Roof



Direct to Outside Straight Duct




Between the Floor Joists




Through the Cabinet Toe Space

### Downward Venting (in inches)




### Rear Wall Venting (in inches)



### Installing the Ductwork

Use galvanized or aluminum duct in 6" round or 3-1/4" x 10" size, or combination of both. **PVC duct or locally approved piping should be used if installing under a poured concrete slab.** Local building code must be followed in specifying type and schedule of all duct used.

**Note:** Ductwork must be vented to outside. Do not vent into a wall, ceiling, crawlspace, attic or any concealed space. Always use an appropriate roof or wall cap with damper. **Laundry-type wall caps should never be used.** For maximum efficiency use the shortest and straightest duct run possible, with as few fittings as possible. For satisfactory performance the duct run should not exceed 100 feet equivalent length. Refer to the table of equivalent lengths (shown in installation instructions) for various duct configurations.



#### Preparing the Cabinet for Installation

In some cabinets, the sides may need to be scooped or cut down 5-3/4" as shown (right) and the corner braces removed in order to accommodate the cooktop.


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.




# Built-In Cooktops: 30" Gas Downdraft

## Model JGP989 Dimensions (in inches)

### Built-In Gas Downdraft Cooktop Dimensions (in inches)




### Built-In Gas Cutout Dimensions (in inches)



Note: A 5" minimum spacing to adjacent side wall is required


### Built-In Gas Cabinet Dimensions (in inches)



#### Receptacle Location

Install an approved junction box within shaded area shown in diagram. Junction box must be at least 10-1/2" below top of cabinet.

### Built-In Gas Downdraft Cooktop Venting Options



#### Wall Installation

Wall installations require 25" countertop depth. When cabinet is flush against the wall, the fan housing can be rotated to the horizontal position for direct venting through rear wall. Make a countertop cutout in the range cabinet according to unit dimensions and installation type. Duct hole is positioned in back of cabinet for through-the-wall ducting.

#### Peninsula or Island Installation

For peninsula/islands a minimum 26" countertop depth is suggested. Blower should be in vertical position. Island or peninsula cabinets may require adjustment in cutout depth and/or location within the width dimensions. Duct hole is positioned in bottom of cabinet for island or peninsula installation.

#### Slab Installation

For peninsula or island installation and rear wall ducting, **6" PVC duct or locally approved piping should be used if installing under a poured concrete slab.**


#### Installing the Ductwork

Use galvanized or aluminum duct in 6" round or 3-1/4" x 10" size, or combination of both. **PVC duct or locally approved piping should be used if installing under a poured concrete slab.** Local building code must be followed in specifying type and schedule of all duct used.

**Note:** Ductwork must be vented to outside. Do not vent into a wall, ceiling, crawlspace, attic or any concealed space. Always use an appropriate roof or wall cap with damper. **Laundry-type wall caps should never be used.** For maximum efficiency use the shortest and straightest duct run possible, with as few fittings as possible. For satisfactory performance the duct run should not exceed 100 feet equivalent length. Refer to the table of equivalent lengths (shown in installation instructions) for various duct configurations.

**Note:** Electrical cable is not supplied with unit. Optional accessories may be ordered for installation on rear wall.


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.




#### Preparing the Cabinet for Installation

In some cabinets, the sides may need to be scooped or cut down 5-3/4" as shown (right) and the corner braces removed in order to accommodate the cooktop.

### Built-In Gas Downward Venting (in inches)




### Built-In Gas Rear Wall Venting (in inches)



# Built-In Cooktops: Downdraft Electric Select-Top™ Modular

## Model JP389 Dimensions (in inches)

### Built-In Downdraft Cooktops Dimensions (in inches)



### Cooktop Options

GE lets you customize your cooktop with flexible modules to suit your taste. Modules must be purchased separately for JP389—they are not included. These optional versatile modules—*Grill, Coil, Ribbon, Griddle Opening Accessory and Grill Cover*—are available at additional cost. Simply plug the modules you want into either side of the cooktop (single modular cooktops accept modules on left side only) and unplug them for easy cleaning and storage.

**Grill Module, JXDL44N** Includes front/rear controlled heating element, one-piece grill grate, and porcelain-enameled reflector pan.

**Griddle Accessory, JXDD44R** (Use with optional Grill Module.)

Place over heating element and reflector pan from optional grill module. Griddle accessory has a non-stick coating and is self-draining.


**Ribbon Modules** Patterned glass top with one 8" and one 6" ribbon heating element. JXDR50VW—White on white, JXDR50VB—Black on black,

**Coil Modules** One 8" and one 6" plug-in heating element with one-piece bowls JXDC43RBL—Black porcelain-enameled JXDC44RWH—White porcelain-enameled

**JXCK89 Electrical Connection Kit.** Optional accessory kit for JP389 electric downdraft cooktop only, includes junction box and conduit.

**Note:** These cooktops are U.L. approved for indoor use only.


### Cutout Dimensions (in inches)



\*U.L. Requirement.

**Note:** A 6" minimum spacing to adjacent side wall is required

### Cabinet Dimensions (in inches)



### Receptacle Location

Install an approved junction box within shaded area shown in diagram. Junction box must be at least 10-1/2" below top of cabinet.

### Preparing the Cabinet for Installation

In some cabinets, the sides may need to be scooped or cut down 2" as shown (right) and the corner braces removed in order to accommodate the cooktop.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

### Wall Installation

Wall installations require 25" countertop depth. When cabinet is flush against the wall, the fan housing can be rotated to the horizontal position for direct venting through rear wall. Make a countertop cutout that is centered in the range cabinet according to unit dimensions and installation type. Duct hole is positioned in back of cabinet for through-the-wall ducting.

### Peninsula or Island Installation

For peninsula/islands a minimum 26" countertop depth is suggested. Blower should be in vertical position. Island or peninsula cabinets may require adjustment in cutout depth and/or location within the width dimensions. Duct hole is positioned in bottom of cabinet for island or peninsula installation.

### Slab Installation


For peninsula or island installation and rear wall ducting, **PVC duct or locally approved piping should be used if installing under a poured concrete slab.**

### Installing the Ductwork


Use minimum 26-gauge galvanized or 24-gauge aluminum duct in 6" round or 3-1/4" x 10" size, or combination of both. **PVC duct or locally approved piping should be used if installing under a poured concrete slab.**

**Note:** Ductwork must be vented to outside. Do not vent into a wall, ceiling, crawlspace, attic or any concealed space. Always use an appropriate roof or wall cap with damper. **Laundry-type wall caps should never be used.** For maximum efficiency use the shortest and straightest duct run possible, with as few fittings as possible. For satisfactory performance the duct run should not exceed 100 feet equivalent length. Refer to the table of equivalent lengths (shown in Pub. No. 49-8552) for various duct configurations.


### Venting Options



### Downward Venting (in inches)



### Rear Wall Venting (in inches)




Listed by  
Underwriters  
Laboratories


# Built-In Cooktops: Downdraft Gas Modular

## Model JGP979 Dimensions (in inches)


### Cabinet (Dimensions in inches)



### Cooktop—JGP979 (Dimensions in inches)




### Cutout



**Gas & Electrical Location** The position of the electrical supply receptacle and the gas supply pipe entering the cabinet should be positioned as shown in the shaded areas. The cooktop is equipped with a 4' power cord, which should reach any desired location on the cabinet walls.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

### Venting Options



**Note:** Ductwork must be vented to outside. Do not vent into a wall, ceiling, crawlspace, attic or any concealed space. Always use an appropriate roof or wall cap with damper. **Laundry-type wall caps should never be used.** For maximum efficiency use the shortest and straightest duct run possible, with as few fittings as possible. For satisfactory performance the duct run should not exceed 100 feet equivalent length.

### Optional Modules (Available at additional cost)

Two-Burner Gas Module (standard burners)—JXGB79W—White on white, JXGB79B—Black on black

Gas Grill Module—JXGG79

Griddle—JXGL79 (use with optional Grill module)

Grill Cover—JXGC89W—White on white, JXGC89B—Black on black

### Wall Installation

Wall installations require 25" countertop depth. When cabinet is flush against the wall, the fan housing can be rotated to the horizontal position for direct venting through rear wall. Make a countertop cutout that is centered in the range cabinet according to unit dimensions and installation type. Duct hole is positioned in back of cabinet for through-the-wall ducting.

### Peninsula or Island Installation

For peninsula/islands a minimum 26" countertop depth is suggested. Blower should be in vertical position. Island or peninsula cabinets may require adjustment in cutout depth and/or location within the width dimensions. Duct hole is positioned in bottom of cabinet for island or peninsula installation.

### Slab Installation

For peninsula or island installation and rear wall ducting, a 6" PVC duct or locally approved piping should be used if installing under a poured concrete slab.

# Slide-In and Drop-In Ranges



## Electrical & Gas Information

Electrical ground is required for electric models. Grounded electrical outlet is required for gas models. Proper gas supply is required for gas models. Check with your local utilities for electrical codes that apply in your area.

## Installation Information

30" slide-in ranges conform to U.L. requirements for 0" spacing from range to adjacent walls below countertop. To reduce the possibility of scorching of the side wall adjacent to the heating elements, it is recommended a minimum 6" spacing from adjacent side walls be allowed for possible extended high-heat, no load heating element operation.

Cabinets installed adjacent to slide-in electric ranges must have an adhesion spec of at least a 194°F temperature rating.

**Receptacle location** for all 30" slide-in ranges locally approved flexible service cord or conduit must be used because terminals are not accessible after range installation. See shaded area in drawing for location of electrical outlet box. Recommended outlet locations allow range to be installed directly against the wall.


**Drop-in ranges** are designed to hang from the countertop. The range does not rest on the floor.

**Over-the-range microwave ovens** can be installed above range as per manufacturer's installation instructions.


Note: Be sure anti-tip device is installed properly.

# Slide-In Ranges: 30" Electric


## Models JS968, JSP57 and JSP47 Dimensions (in inches)



If you are NOT using the optional Filler or Backguard:



If you are using the optional Filler or Backguard:



### Optional Kits for Slide-In Electric Ranges (Models JS968, JSP57 and JSP47) (Available At Additional Cost)

**Accessory Backguards**  
(Attaches to the back of range as a backguard when unit is installed in 30" free-standing cutout)  
JXS39SS—Stainless  
JXS36WW—White  
JXS36CC—Bisque  
JXS36BB—Black

### Body Sides

(Slide-in ranges are sold without sides installed. Can be installed on either left or right when unit has one exposed side [no cabinet adjacent]. Kit contains 1 body side)  
JXS76WW—White  
JXS76CC—Bisque  
JXS76BB—Black

### Vertical Side Trim Kits

(If cabinet cutout width is more than 30", a vertical side trim kit may be used to close the gap between the range and cabinet)  
JXS86WW—White  
JXS86CC—Bisque  
JXS86BB—Black

### Lower Trim Kits

(If counter height is greater than 36.5", a lower trim kit is recommended to extend the useful height to 38" maximum)  
JXS56WW—White  
JXS56CC—Bisque  
JXS56BB—Black



All GE ranges are equipped with an Anti-Tip device. The installation of this device is an important, required step in the installation of the range.




Listed by  
Underwriters  
Laboratories



# Slide-In Ranges: 30" Electric

## Models JSP34, JSP26, JSS26 and JSS16 Dimensions (in inches)



### Optional Kits for Slide-In Electric Ranges (Models JSP34/26 and JSS26/16)

(Available at additional cost)

#### Rear Filler Strip Kit

JXS28—Rear Filler Strip Kit (Brushed-chrome)

#### Accessory Backguards

JXS31—White Accessory Backguard

JXS32—Brushed-Chrome Accessory Backguard

JXS34—Black Accessory Backguard

JXS35—Bisque Accessory Backguard

#### Endcap Kit

JXS40—Endcap kit to accommodate replacement where countertop may already be notched.

### Lower/Side Trim Kits

(If countertop height is greater than 37", it is recommended to use a lower trim kit.)

JXS52BB—Lower trim (Black)

JXS53WWW—Lower trim (White)

JXS55CC—Lower trim (Bisque)

Pub. No. 3-A040—Vertical Side Trim Kit (Brushed-Chrome)

**Models shown are shipped with rear filler strip kit.**

**Note:** Range may be placed with 0" clearance (flush) at the back wall and side walls if the range side trims extend beyond the cabinet fronts at least 1/4". (Self-clean models only)

**Note:** Cabinets installed adjacent to slide-in electric ranges must have an adhesion spec of at least a 194°F temperature rating.


**Important:** Before installing, consult installation instructions packed with product for current dimensional data.



# Slide-In Ranges: 30" Gas and Dual-Fuel

## Models J2S968, JGS968, JGSP48, JGSP23 and JGSS05 Dimensions (in inches)

### 30" Slide-In Gas Ranges Dimensions (in inches) Models J2S968, JGS968, JGSP48 and JGSP23




| Dimensions (in inches) |    |        |        |        |                  |
|------------------------|----|--------|--------|--------|------------------|
| Model                  | A* | B      | C**    | D      | E                |
| J2S968                 | 30 | 38     | 28     | 44-3/4 | 35-3/4 to 36-1/2 |
| JGS968                 | 30 | 38     | 28     | 44-3/4 | 35-3/4 to 36-1/2 |
| JGSP48                 | 30 | 38     | 28     | 44-3/4 | 35-3/4 to 36-1/2 |
| JGSP23                 | 30 | 36-1/4 | 28-7/8 | 45-1/8 | 35-7/8 to 38     |

\*Cooktop width including overhang 30-3/4".  
\*\*Depth including handle:  
25-1/2"—Wall to front of closed oven door  
26-1/4"—Depth to front top edge of control panel


### Model JGSP23

Recommended area for 120V outlet on rear wall and area for through the wall connection of pipe stub and shut-off valve




Recommended area for through the floor connection of pipe stub and shut-off valve


### Models J2S968, JGS968 and JGSP48



### 30" Slide-In Gas Range Dimensions (in inches) Model JGSS05




\*Depth to front of closed oven door  
28-1/4" depth including handle  
25-1/4" depth to front top edge of cooktop




### Counter Cutout Dimensions (in inches) Models J2S968, JGS968, JGSP48 and JGSP23

If you are NOT using the optional Filler or Backguard:




If you are using the optional Filler or Backguard:



You must use the rear filler strip kit shipped with the range or the optional accessory backguard (JXS31, JXS32, JXS33, JXS34) when installing these ranges.

**Note:** Cabinets installed adjacent to slide-in ranges must have an adhesion spec of at least 194°F temperature rating.



\*ANSI Requirement

### Optional Kits for Slide-In Gas Ranges: (Available at additional cost)

#### Rear Filler Strip Kits

Model 9JGSP23 is shipped with required "vented" rear filler strip.

#### Lower/Side Trim Kits

JXS52BB—Lower Trim Kit (Black)  
JXS53WW—Lower Trim Kit (White)  
JXS55CC—Lower Trim Kit (Bisque)

#### Accessory Backguards

JXS31—White Accessory Backguard  
JXS32—Brushed-Chrome Accessory Backguard  
JXS34—Black Accessory Backguard  
JXS35—Bisque Accessory Backguard

#### Endcap Kit

JXS40—Endcap kit to accommodate replacement where countertop may already be notched.

### Optional Gas Range Wok Accessory: (Available at additional cost)

JXWK—Wok Accessory Holder sits on top of maximum burner grate to hold a round bottom wok.

**Note:** Model JGSP23 is shipped with special "vented" rear filler strip. Post form countertops may not be used when installing this range. The filler strip (provided) or optional backguard kit is required for installation.




# Drop-In Ranges: 27" Electric

## Models JMP31, JMP28 and JMS08 Dimensions (in inches)


**Important:** This range is designed to hang from the countertop. It does not rest on the floor.

If necessary, build up sides to 1-1/2" thick to provide screw anchor surface and countertop support

These screws are anti-tip devices and must be installed in the front and rear



### Countertop Cutout-Top View



**Note:** All 30" Drop-In Radiant Ranges conform to U.L. requirements for 0" spacing from range to adjacent walls below countertop. To reduce possibility of scorching the side walls above the countertop when no load is present on burners, it is recommended that a minimum 6" spacing from adjacent side wall be allowed for possible extended high-heat element operation.

**Note:** Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°F temperature rating.

### Optional Backguard

(Available at additional cost)

JX27RBK = Black

JX27RWH = White

JX27RAD = Almond

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

\*If countertop edge is formed, this dimension must extend to flat area

In replacement installation, use JX27R optional backguard, if required



Listed by  
Underwriters  
Laboratories

# Ventilation Options



## Venting

*Electrical ground is required.*

Use dimensions for ductwork cutout that apply to your hood model. Ducted hoods must always be vented to the outdoors.

## Telescopic Downdraft Systems


Install downdraft system first before installing cooktop. See cooktop installation instructions for cutout depth and width.

The countertop must be at least 26" deep with a flat surface of 23-1/2" or more, front to back. In addition, other clearances to the front edge of the countertop must be considered.


# Designer Hoods: 36" and 30"

## Models JV966, JV965, JV936 and JV935 Dimensions (in inches)

Installed above a cooktop (in inches)  
Shown with optional chimney kit



Installed above a range (in inches)  
Shown with optional chimney kit



### Optional Kits for 36" Designer hoods


JXBF36SS—36" Commercial Filter  
JXCHSS—Stainless Chimney Kit  
JXCHWW—White Chimney Kit  
JXCHCC—Bisque Chimney Kit  
JXCHBB—Black Chimney Kit

### Optional Kits for 30" Designer hoods

JXBF30SS—30" Commercial Filter  
JXCHSS—Stainless Chimney Kit  
JXCHWW—White Chimney Kit  
JXCHCC—Bisque Chimney Kit  
JXCHBB—Black Chimney Kit

## Slide-Out Hoods

## Models JV960, JV930, JV696, JV695, JV694, JV396, JV395 and JV394 Dimensions (in inches)




### Notes:


These vented hoods include an installed damper.  
The unit is ducted vertically. Horizontal ducting can be accomplished as shown.  
Remove glass visor from unit before installing hood in cabinet to protect visor from damage.

**Important:** Before installing, consult installation instructions packed with product for current dimensional data.

### Cabinet



Flush bottom cabinet




Recessed bottom cabinet



Listed by  
Underwriters  
Laboratories

# Hoods: 36" and 30"


## 1 Models JV666C, JV665C, JV636C, JV635C, JV536C, JV535C, JV566C and JV565C Dimensions (in inches)



Exhaust outlet connects to 3-1/4" x 10" duct (vertically or horizontally) and 7" round (vertically). Includes rectangular damper and 7" round damper adapter.


Round damper accessory, JXDA23 available at additional cost. JV535, JV536, JV565 and JV566 are 4-way convertible.

## 2 Models JV347H\* and JV338H Dimensions (in inches)




\*JV347H and JV338H—Refer to this drawing for rectangular exhaust option. Refer to drawing 3 for round exhaust option. Exhaust outlet connects to 3-1/4" x 10" rectangular duct. Vent top or rear. Includes rectangular damper.

## 3 Models JV347H\* and JV338H Dimensions (in inches)




\*JV347H and JV338H—Refer to this drawing for round exhaust option. Refer to drawing 2 for rectangular exhaust option. Exhaust outlet connects to 7" diameter duct. Vent top only. Round damper accessory, JXDA22, available at additional cost.

## 4 Model JN327H Dimensions (in inches)



### JXHC1 cord kit

Allows a receptacle in the cabinet over the range to accommodate either an OTR or a standard hood.



| Dimensions (in inches) |       |        |        |    |
|------------------------|-------|--------|--------|----|
| Model                  | A     | B      | C      | D  |
| JV666/JV665            | 7-1/4 | 35-7/8 | 20     | 12 |
| JV636/JV635            | 7-1/4 | 29-7/8 | 20     | 12 |
| JV536/JV535            | 7-1/4 | 29-7/8 | 20     | 12 |
| JV566/JV565            | 7-1/4 | 35-7/8 | 20     | 12 |
| JV347                  | 5-1/2 | 29-7/8 | 17-1/2 | 12 |
| JV338                  | 5-1/2 | 29-7/8 | 17-1/2 | 12 |
| JN327                  | 5-1/2 | 29-7/8 | 17-1/2 | 12 |

**Installation Information:** Before installing, consult installation instructions packed with product for current dimensional data.




(Models JV347 and JV338 only)




# Telescopic Downdraft Systems: 36" and 30"

## Models JVB96SA and JVB93SA Dimensions (in inches)




|       | A   | B       |
|-------|-----|---------|
| JVB96 | 36" | 32-1/4" |
| JVB93 | 30" | 26-1/4" |

## Venting Island to Outside Wall




## Models JVB67A and JVB37A Dimensions (in inches)




|       | A   | B                 |
|-------|-----|-------------------|
| JVB67 | 36" | 17-1/8" – 28-5/8" |
| JVB37 | 30" | 14-3/8" – 17-7/8" |

## Blower Position



## Counter Cutout Information Models JVB96, JVB93, JVB67 and JVB37



Pay special attention to the four areas of potential interference circled above 2" of **FLAT** countertop is needed behind rear edge of cooktop to accommodate downdraft vent cover (required to maintain U.L. or AGA approvals). **It is recommended that gas and/or electrical service for cooktop and downdraft should be in adjacent cabinet to right.**

Approved for use with the following GE cooktops—36" and 30" Calrod® models, 36" and 30" radiant models, 30" solid disk models, 36" and 30" induction models and 36" and 30" gas sealed burner models.



# Telescopic Downdraft Systems: 36" and 30"

**Note:** Telescopic downdraft vents are not recommended to be installed with cooktops that are flush mounted.

Approved for use with the following GE Profile™ and GE® cooktops—36" and 30" electric models, 36" and 30" gas sealed burner models and 36" and 30" induction models.

**Not approved for use with standard burner gas cooktops.**

**Note:** The countertop must be at least 26" deep with a flat surface area of 23-1/2" or more, front to back. In addition, other clearances to the front edge of the countertop must be considered.

**Note:** Dimensions shown are for reference only. Before cutting out countertop, refer to instructions packed with **downdraft and cooktop**.

**Note:** Installation in cabinets/countertops against the wall will not be possible in most applications. Against the wall installations are limited to dimension requirements. Refer to installation instructions packed with product for further details.


**JXBC57 Outdoor Cover (JVB67/37 Only).** Optional accessory may be ordered for installation of motor and blower assembly on outside wall.

**JXRB57 Indoor Remote Accessory (JVB67/37 Only).** Optional accessory may be ordered for installation of motor and blower assembly in an indoor remote location.


**Installation Information:** Before installing, consult installation instructions packed with product for current dimensional data.

## Models JVB96, JVB93, JVB67 and JVB37 Dimensions (in inches)


### Through the Floor Venting




### In Cabinet Discharge (Down) Venting


















### In Cabinet Discharge (Right) Venting



### In Cabinet Discharge (Left) Venting



| Duct Pieces  | Equivalent Length*      | Duct Pieces   | Equivalent Length* | Duct Pieces   | Equivalent Length* |
|--|-------------------------|---|--------------------|---|--------------------|
|  6" Round Straight      | 1 ft. (per foot length) |  3-1/4" x 10" 45° Elbow                        | 5 ft.              |  3-1/4" x 10" to 6" Round Transition 90° Elbow | 12 ft.             |
|  3-1/4" x 10" Straight  | 1 ft. (per foot length) |  3-1/4" x 10" 90° Flat Elbow                   | 24 ft.             |  6" Round Wall Cap with Damper                 | 21 ft.             |
|  6" 90° Elbow           | 15 ft.                  |  6" Round to 3-1/4" x 10" Transition           | 7 ft.              |  3-1/4" x 10" Wall Cap with Damper             | 27 ft.             |
|  6" 45° Elbow           | 9 ft.                   |  3-1/4" x 10" to 6" Round Transition           | 5 ft.              |  6" Round Roof Cap                             | 20 ft.             |
|  3-1/4" x 10" 90° Elbow | 16 ft.                  |  6" Round to 3-1/4" x 10" Transition 90° Elbow | 20 ft.             |  6" Round Roof Vent                            | 24 ft.             |

\*Should Not Exceed 150 Equivalent Ft.  
Equivalent lengths of duct pieces are based on actual tests conducted by GE Evaluation Engineering and reflect requirements for good venting performance with any downdraft cooktop, with a downdraft rated at 500-CFM.



Answers that click!  
GE puts everything you need at your fingertips.



**GE Appliances web site — 16 million visitors a year!**  
**Visit us at [GEAppliances.com](http://GEAppliances.com)**

Everything you need to know about GE products is here. Access up-to-date information, find out "what's new," obtain dimensions, get installation tips and more. Extremely user-friendly, this one-stop site lets you research by brand, category or model number and even buy online through a local GE dealer.

**GE Answer Center® saves you time.**  
**800.626.2000**

This 24-hour-a-day, 7-day-a-week service provides answers on product features, installation, service and more.



## A Century of Quality and Innovation

For more than a century, GE has been committed to producing innovative products that change the way people live. The result of thorough research and rigorous testing, GE appliances are designed for years of dependable performance. Today, the GE tradition of quality and innovation continues.



**GE Appliances**

GE Consumer Products  
General Electric Company  
Louisville, Kentucky 40225  
[GEAppliances.com](http://GEAppliances.com)

GE has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.

© 2003 General Electric Company  
Pub. No. 3-X133 PC34724