### **PHP7036DT**

## GE Profile™ 36" Built-In Touch-Control Induction Cooktop


### **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**

**IMPORTANT:** Requires a 3" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

NOTE: 36" induction cooktops are approved for use over select GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered.

Before installing, consult installation instructions packed with product for current dimensional data.


### APPROXIMATE COOKING DIMENSIONS



To insure accuracy, it is best to make a template when cutting the opening in the counter

### 13" MAX. depth of unprotected overhead cabinets 2" MIN. Clearance from cutout to nearest vertical wall or cabinet on right side of the unit below the 15" MIN. clearance height. 30" MIN. Clearance from countertop to unprotected overhead surface See label next to nameplate for MIN. clearance to rear wall 15" MIN. height from countertop to nearest cabinet (including light rails) on both sides of 2" MIN. clearance cooktop to side wall from cut-out on the left of the unit

#### **INSTALLATION ABOVE A WALL OVEN**



KW RATING	
240V	11.6
208V	10.1
AMPERAGE	
240V	50 Amps <sup>†</sup>

\*NOTE: Check local codes for required breaker size.









For answers to your Monogram, GE Café™, GE Profile™ or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service. 800.626.2000.

### **PHP7036DT**

# GE Profile™ 36" Built-In Touch-Control Induction Cooktop

### **FEATURES AND BENEFITS**

Maximum Responsiveness - 11 Control Levels

Power Boil

Precision Temperature Control

Easy Clean Surface

Safe Surface

Most Efficient Heating

Synchronized Elements

Chef Connect

Compatible Cooktop with Smart


Timer

Built-in WiFi

Control Lock

Fit Guarantee

Model PHP7036DTBB - Black on black



### COMPATIBLE COOKTOP WITH SMART COOKWARE

Smart pans easily pair with this smart cooktop to ensure you get the perfect cooking results. Accessories sold separately.

#### **OPTIONAL SOUS VIDE PROBE**

A Sous Vide Probe lets you achieve great results on the stove. Order part number JXPROBE1.

#### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications.

Visit geappliances.com for more info.

