PDW9800/9880L

GE Profile™ Fully Integrated Built-In Dishwasher with Stainless Interior

Dimensions and Installation Information (in inches)

Electrical Rating

Voltage AC	120
Hertz	60
Total connected load amperage	9.1
Calrod® heater watts max	875

For use on adequately wired 120-volt, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be grounded for safe operation.

Installation Information: Before installing, consult installation instructions packed with product for current dimensional data.

†† Add 1/2" for deepest part of contour door. Allow an additional 2" for the handle on PDW9900/9800/9200 Series models.

24-3/4^{††} 22-1/2 27-1/2 33-13/16" MIN. adj. to 35" 21-1/4 Countertop This wall area 90° 4 (Adjustable) must be free of pipes or wires 24" 3-1/2 Electrical MIN. wiring is 3" from cabinet Hot Electrical water 34" to 34-3/4" Underside line on wiring on left right of countertop to floor Plumbing and electrical service must enter inside shaded area 24" MIN.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.







partner, GE has determined that this product meets the ENERGY STAR quidelines for energy efficiency.

PDW9800/9880L

GE Profile™ Fully Integrated Built-In Dishwasher with Stainless Interior

Features and Benefits

- Stainless Contour Door with Stainless Sculptured Handle and Hidden Controls Creates an elegant appearance with a sleek stainless steel door and handle while
 hiding the controls inside the top edge of the dishwasher door (Model PDW9880LSS)
- Giant Tub with Maximum Capacity Nylon Racking Holds tall and oversized items; washes 16 place settings at once
- Countdown Display with 1-24 Hour Delay Start Signals remaining cycle time and starts the dishwasher when no one's home or during off peak hours when utilities are at a reduced rate
- Four-Position Adjustable/Removable Upper Rack Pulls out completely or moves up, down and diagonally for maximum loading flexibility
- 3 Nylon-Coated Pearlescent™ Metal Utility Shelves with StemSafe™ in Upper Rack Durable metal shelves create space in the upper rack for cups and utensils and secure delicate stemware
- 100% Fold-Down Tines and Adaptable Bowl Tines in Lower Rack Flip up to hold bowls, or flip down to provide maximum loading flexibility in the lower rack
- Audible End-Of-Cycle Signal When on, emits an audible signal to indicate the cycle has ended
- QuietPower™ 6 Sound Package Preserves peace and quiet in the kitchen with fan-assisted drying and an enhanced insulation package
- Cutlery Tray Protects cutlery or flatware and leaves space underneath for more dishes
- Model PDW9880LSS Stainless steel (shown)
- Model PDW9800LWW White on white
- Model PDW9800LBB Black on black



