# PDW9900/9980N

## GE Profile<sup>™</sup> Dishwasher with SmartDispense<sup>™</sup> Technology

#### Dimensions and Installation Information (in inches)

### **Electrical Rating**

Voltage AC	120
Hertz	60
Total connected load amperage	9.1
Calrod® heater watts max	875

For use on adequately wired 120-volt, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be grounded for safe operation.

**Installation Information:** Before installing, consult installation instructions packed with product for current dimensional data.

†† Add 1/2" for deepest part of contour door. Allow an additional 2" for the handle on PDW9900/9200 Series models.

24-3/4 22-1/2 27-1/2 33-13/16" MIN. adj. to 35" 21-1/4 Countertop This wall area must be free of → 90° pipes or wires 4" (Adjustable) 24" Electrical MIN. 3-1/2 wiring is 3" from cabinet Hot water Electrical 34" to 34-3/4" line on wiring on Underside right left of countertop Plumbing and electrical service must enter inside shaded area 19" MIN. from wall 24" From wal 24" MIN.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.









### PDW9900/9980N

### GE Profile™ Dishwasher with SmartDispense™ Technology

#### **Features and Benefits**

- SmartDispense™ Technology Holds an entire bottle of liquid automatic dishwasher detergent, dispensing the right amount based on water hardness and soil levels to get dishes incredibly clean
- Angled Rack Dry<sup>™</sup> System Features tines that gently angle cups, mugs and dessert glasses so water runs right off
- Single Rack Wash™ Selection Perfect for smaller loads or for cleaning glasses only, washing just the upper rack of dishes using less water and energy
- QuietPower™ 7 Sound Package Our quietest dishwasher ever with extremely quiet components and a hidden vent that seals in sound during the wash cycle
- Countdown Display with 1-24 Hour Delay Start Signals remaining cycle time and starts the dishwasher when no one's home or during off peak hours when utilities are at reduced rates
- 100% Fold-Down Tines and Adaptable Bowl Tines in Lower Rack Flip up to hold bowls, or flip down to provide maximum loading flexibility in the lower rack
- SpeedCycle<sup>™</sup> Selection Cuts the length of the normal cycle in half, effectively washing and drying lightly soiled dishes in about 45 minutes or less
- Model PDW9980NSS Stainless steel (shown)
- Model PDW9900NWW White on white
- Model PDW9900NBB Black on black



