PDWT100/180R

GE Profile™ Stainless Interior Built-In Dishwasher with Hidden Controls

Dimensions and Installation Information (in inches)

Electrical Rating

Voltage AC	120
Hertz	60
Total connected load amperage	9.1
Calrod® heater watts max	875

For use on adequately wired 120-volt, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be grounded for safe operation.

Installation Information: Before installing, consult installation instructions packed with product for current dimensional data.

†† Add 1/2" for deepest part of contour door. Allow an additional 2" for the handle on PDWT500/PDWT400/PDWT200 Series models.

24-3/4* 22-1/2 27-1/2 33-13/16" MIN. adj. to 35" 21-1/4 Countertop This wall area 90° must be free of → 4" (Adjustable) pipes or wires 24" 3-1/2 Electrical MIN. wiring is 3" from cabinet Hot water Electrical 34" to 34-3/4" line on wiring on Underside right left of countertop Plumbing and electrical service must enter inside shaded area 19" MIN. from wall 24" From wal 24" MIN.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800 626 2000.







As an ENERGY STAR® partner, GE has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

PDWT100/180R

GE Profile™ Stainless Interior Built-In Dishwasher with Hidden Controls

Features and Benefits

- PureClean wash system with 5-stage filtration Multiple filtration levels ensure clean dishes
- ENERGY STAR® Qualified Meets or exceeds federal guidelines for energy efficiency for year-round energy and money savings
- CleanSensor[™] A tiny laser measures soil levels and water temperature to adjust to the ideal cycle time
- Steam Pre-Wash option Steam helps to loosen tough soils before any cycle
- Eclipse black nylon deep-tiered rack Durable racks are designed to resist rust and secure dishes
- Electronic controls with 3 cycles/5 options Modern controls make it easy to program the dishwasher
- QuietPower[™]52 sound package 52 dBA An enhanced sound-deadening system muffles noises and keeps the kitchen quiet
- Anti-bacterial selection Cycle raises temperature up to 151°F to sanitize dishes, baby bottles and sippy cups
- Model PDWT180RSS Stainless steel (shown)
- Model PDWT100RWW White on white
- Model PDWT100RBB Black on black



