




GE Appliances

AZ38H15E – GE Zoneline® Deluxe Series Heat Pump Unit

Wall Case Dimensions




RAB71 Wall Sleeve

Heavy-gauge galvanized steel, with insulation.
A – 42", B – 13-3/4", C – 16"

RAB77 Wall Sleeve

Molded SMC fiberglass-reinforced polyester compound.
A – 42-1/8", B – 13-7/8", C – 16-1/4"

Maximum Cord Extension (in inches)



Wall Opening Dimensions

Add 1/4" to A and C dimensions for all cut-out size.
RAB71 16-1/4" Min. H x 42-1/4" Min. W
RAB71 available in 16", 24", 28" and 31" depths
RAB77 16-1/2" Min. H x 42-3/8" Min. W

Electrical Wiring

All wiring, including installation of receptacle, must be made in accordance with local electrical codes and regulations.

Note: Aluminum wiring may pose special problems – consult a qualified electrician.

Grille Options

Stamped Aluminum Grille – RAG60

Exterior Architectural Louvers Durable Polycarbonate:

RAG61 or RAG64 (Beige) RAG63 or RAG66 (Bittersweet)
RAG62 or RAG65 (Maple) RAG67 (Extruded Aluminum)

Retrofit Kits:

RAK901L – Wall Case Insulation for use with heat pumps.
RAK40 – Deflector Kit to adapt chassis for use with existing exterior architectural louvered grilles.

Ducted Applications

2800 and 3800 series can be used with ductwork to heat or cool more than one room. RAK6052 Duct Adaptor is applied to top of case over air discharge/RAK601 Duct Extension is applied to right or left of adaptor. Locally fabricated ductwork may be added to extend to maximum recommended distance of 15 feet.

Electrical Connection

230/208 volt units may be plugged into a receptacle. 265 volt units are provided with a junction box and require direct connection. (NEC Requires 265V Direct Connection) See Architects and Engineers Design Data Manual for electrical connection information including use of sub-base for direct connected units. Installation must comply with local electrical codes and regulations.

Power Connection kits required on all Zoneline chassis.


For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.

| 265 Volt Sub-Base Connected Units | | | | |
|-----------------------------------|----------------------|-----------------------|--------------------|--------------------------------|
| Sub-Base | Power Connection Kit | Electric Heater Watts | Electric Heat Amps | Min. Circuit Protection (Amps) |
| RAK204E15 | RAK5172 | 2,550 | 10.3 | 15 |
| RAK204E20 | RAK5202 | 3,450 | 13.7 | 20 |
| RAK204E30 | RAK5302 | 5,000 | 19.6 | 30 |



GE Appliances

AZ38H15E – GE Zoneline® Deluxe Series Heat Pump Unit



Features and Benefits

- 14,600 BTUH (Cooling)
- 10.0 E.E.R.
- 4.5 Dehumidification (pts/hr)
- 13,400 BTUH (Reverse Cycle Heat)
- 310/260 CFM Indoor Fan (High/Low)
- 75/45 Vent CFM
- Electronic 7-Step Temperature Limiting To Prevent Overcooling or Overheating of Room
- Heat Sentinel
- Reverse Cycle Heating
- 29 Sound Transmission Class (STC)
- Standard Microcomputer, Rotary Knobs
- Model AZ38H15EAB – Warm grey beige
- Model AZ38H15EAC – Warm grey beige (Corrosion Treated)
- Model AZ38H15EAD – Warm grey beige (Internal Condensate Removal)