
# **AKCQ12DCA**

# GE® 230/208 Volt Built-in Cool-only Room Air Conditioner

### WALL CASE DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**NOTE:** When installing slide-out chassis units in through-the-wall applications, keep louvers free. Do not restrict air flow areas.



Note: When installing units in through-the-wall applications.

Do not restrict air flow areas.





Total volume and shelf area are calculated by the Association of Home Appliance Manufacturers' standards.



### **AKCQ12DCA**

### GE® 230/208 Volt Built-in Cool-only Room Air Conditioner

#### **DIMENSIONS (IN INCHES)**

**INSTALLATION INFORMATION:** A finished opening of 26-1/8" x 15-3/4" clear of intrusions is required. Keep clearance of 4" from side walls. Brick veneer or frame walls should have wood studding surrounding case to provide firm anchoring with screws. Case can be fastened directly to brick or block walls with screws sunk in lead expansion shields.

**NOTE:** Units should be caulked on all four sides of case to the building exterior to assure building integrity.


#### WALL CASE FOR TENANT OPTION INSTALLATION


When the air conditioner is offered as a tenant option, this wall case provides protection against outside elements.

**RAB48** – includes wall case, exterior grille, steel closure panel and two layers of insulation.

#### **STANDARD WALL CASE RAB46**

Solid-sided wall case fabricated of galvanized steel with baked enamel finish. Welded areas are coated with a sealing compound to help resist rust and corrosion. Polymer gasket surrounds opening to assure tight weather seal. Aluminum grille (RAG13) is included. Panels on interior and between case and grille provide weather protection prior to installation of chassis. Provide firm anchoring with screws. Case can be fastened directly to brick or block walls with screws sunk in lead expansion shields.









Total volume and shelf area are calculated by the Association of Home Appliance Manufacturers' standards.



### **AKCQ12DCA**

## GE® 230/208 Volt Built-in Cool-only Room Air Conditioner

#### **FEATURES AND BENEFITS**

Universal Fit – These units are designed for simple installation and fit easily into most existing wall sleeves

Electronic Controls – Easily select options for your air conditioner with easy-to-use controls

Three Fan Speeds – Multiple speed fan makes it simple to program the air conditioner to your ideal comfort setting

Remote Control – Control temperature and fan speed from anywhere in the room with a precise infrared remote control

Programmable 24-hour Timer – Set the air conditioner to turn on or off at the times that best fit your schedule, with a 24-hour timer that can be set in 1-hour increments

Dehumidify Mode – Reduce damp air and improve overall comfort during warm summer months with extra dehumidification. Ideal for use in especially humid regions of the country

Energy Saver Mode – A high-efficiency mode maintains cool temperatures and helps reduce monthly utility bills by cycling on and off at different intervals

Six-Way Air Direction – Enjoy total room comfort by directing air flow to the areas you want to cool the most, with six directions to choose from

Easy-Access Washable Filter – Keep your room smelling fresh and clean with an easy-access filter that can remove airborne particles and help reduce odors

Automatic Restart – Rest assured knowing that in the event of power loss, the unit will resume operation in the same settings that were established before the outage

Clean Filter Alert – Always remember when it's time to clean the filter with an indicator light

Temperature Preset Control - Maintain comfort at a preset temperature

Two-Year Warranty – Enjoy peace of mind knowing your unit is backed by GE Appliances and protected with a full two-year parts and labor warranty

Model AKCQ12DCA - Soft Gray



