



JSP47SH - GE Profile™ 30" Slide-In Electric Range


Dimensions (in inches)






If you are NOT using the optional Filler or Backguard:

If you are using the optional Filler or Backguard:







All GE ranges are equipped with an Anti-Tip device. The installation of this device is an important, required step in the installation of the range.





Note: Cabinets installed adjacent to slide-in electric ranges must have an adhesion spec of at least 194°F temperature rating.

Note: All 30" Slide-In Ranges conform to U.L. requirements for 0" spacing from range to adjacent walls below countertop. To reduce possibility of scorching the side walls above the countertop when no load is present on burners, it is recommended that a minimum 6" spacing from adjacent side wall be allowed for possible extended high-heat element operation.

Receptacle Locations: For all 30" Slide-In Ranges locally approved flexible service cord or conduit must be used because terminals are not accessible after range installation. See shaded area in drawing for location of electrical outlet box. Recommended outlet locations allow range to be installed directly against rear wall.

Optional Kits for Slide-In Electric Ranges (Available at additional costs)

Accessory Backguards

(Attaches to the back of range as a backquard when unit is installed in 30" free-standing cutout) JXS37WW – White JXS37CC – Bisque JXS37BB - Black/Stainless

Body Sides

(Slide-in ranges are sold without sides installed. Can be installed on either left or right when unit has one exposed side Ino cabinet adiacentl. Kit contains 1 body side)

JXS76WW – White

JXS76CC - Bisque

JXS76BB - Black

Vertical Side Trim Kits

(If cabinet cutout width is more than 30", a vertical side trim kit may be used to close the gap between the range and cabinet)

JXS86WW - White

JXS86CC - Bisaue

JXS86BB - Black

Optional Lower Trim Kits

(If counter height is greater than 36.5", a lower trim kit is recommended to extend the useful height to 38" maximum)

JXS56WW - White

JXS56CC - Bisque

JXS56BB - Black

Optional Top Filler Kits

JXS66WW - White

JXS66CC - Bisque

JXS66BB - Black

Installation Information: Before installing, consult installation instructions packed with product for current dimensional data.

For answers to your Monogram.® GE Profile™ or GE® appliance questions, visit our website at GEAppliances.com or call GE Answer Center® service, 800.626.2000.

11.6

8.7

40 Amps

40 Amps

KW Rating

Breaker Size

240V

208V

240V

208V



JSP47SH – GE Profile™ 30" Slide-In Electric Range



Features and Benefits

- Self-clean oven Conveniently cleans the oven cavity without the need for scrubbing
- Electronic oven controls One-touch electronic pads are easy-to-use and allow for simple oven operation
- Dual size ribbon element Offers a convenient choice of using a 6" or 9" heating element, depending on the size of the pan
- Super large oven capacity Provides the impressively large oven interior for cooking more dishes and large meals at one time
- TrueTemp[™] system Delivers even heat distribution and maximum oven control
- Ribbon heating elements Provide the powerful heat beneath a smooth glass surface to ensure even heat and fast warm-up times
- Ceramic glass cooktop A smooth cooktop surface makes cleaning quick and easy
- Model JSP47SHSS Stainless steel