


90% AFUE GAS FURNACES

EASIER TO: DO THE JOB



INSTA-POSITION TECHNOLOGY

For tight crawl spaces or attics that require a horizontal furnace, simplify the installation process and save time with furnaces designed for easy installation in multiple positions, without the need for internal conversions.



BETTER FIT

Standing at just 33" tall, our furnaces are designed to fit into more spaces, occupying less room wherever they're installed.



PRE-FORMED FLANGES

Our coils are designed to align with flanges on matching gas furnaces, reducing installation time and risk of damage.



OPEN-BACKED WIRE CONNECTORS

Our open-backed electrical connections allow you to take readings without disconnecting any wires, saving you time when testing components.

EASIER TO: CLOSE THE SALE



QUIET OPERATION

Designed with smaller, more efficient burners and an insulated heat exchanger compartment that helps prevent any clicks or whooshes during startup.



100,000 CYCLE TESTED HEAT EXCHANGER

When you assure a customer of the durability of GE Appliances, there's no need to cross your fingers. We build and test our products so you can confidently stand behind them.



HIGH-EFFICIENCY

Homeowners can reduce their energy bills with high-efficiency gas furnaces boasting a 95-98% AFUE rating.



ULTRA-LOW-NOX

Ultra-Low NOx units generate reduced nitrogen oxide emissions, helping to mitigate potential health issues and lessen environmental impact.



TEN-YEAR WARRANTY

Double the standard five-year warranty by registering the unit, and receive a lifetime warranty on the heat exchanger. Translation: peace of mind for your homeowners. See warranty documentation for complete details.



GE APPLIANCES

90% AFUE GAS FURNACES SPECIFICATIONS



GE APPLIANCES
a Haier company

AIR & WATER
SOLUTIONS

NF98/97****M Modulating Gas Furnaces

	Model	Efficiency (% AFUE)	Stages	Motor	AHRI Rated BTH/hr Input/Output	Cooling (Nominal Tonnage)	Air flow	Emissions	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
NEW	NF98U070M3B	98%	Modulating	Variable Speed	66/64K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	123.50
	NF98U090M3C	98%	Modulating	Variable Speed	88/85K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	146.30
	NF98U090M4C	98%	Modulating	Variable Speed	88/86K	4	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	146.30
	NF98U090M5C	98%	Modulating	Variable Speed	88/85K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	148.20
	NF98U110M5C	98%	Modulating	Variable Speed	111/106K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	166.25
	NF98U135M5D	98%	Modulating	Variable Speed	132/127K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 24.5 x 28.5	176.70
	NF97U070M3B	97%	Modulating	Variable Speed	66/64K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	123.50
	NF97U090M3C	97%	Modulating	Variable Speed	88/85K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	146.30
	NF97U090M4C	97%	Modulating	Variable Speed	88/86K	4	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	146.30
	NF97U090M5C	97%	Modulating	Variable Speed	88/85K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	148.20
	NF97U110M5C	97%	Modulating	Variable Speed	111/106K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	166.25
	NF97U135M5D	97%	Modulating	Variable Speed	132/127K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 24.5 x 28.5	176.70
	NF97D070M3B	97%	Modulating	Variable Speed	66/64K	3	Downflow	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF97D090M4C	97%	Modulating	Variable Speed	88/85K	4	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	157.70
	NF97D110M5C	97%	Modulating	Variable Speed	110/107K	5	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	165.30

Note: Maximum efficiency and capacity performance ratings shown. Actual performance may vary by equipment matchup selection.

NF97/96****V 2-Stage Gas Furnaces

	Model	Efficiency (% AFUE)	Stages	Motor	AHRI Rated BTH/hr Input/Output	Cooling (Nominal Tonnage)	Air flow	Emissions	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
NEW	NF97U045V3B	97%	2-Stage	Variable Speed	44/42K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF97U070V3B	97%	2-Stage	Variable Speed	66/62K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF97U090V3C	97%	2-Stage	Variable Speed	88/84K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	145.35
	NF97U090V5C	97%	2-Stage	Variable Speed	88/85K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	156.75
	NF97U110V5C	97%	2-Stage	Variable Speed	110/106K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	166.25
	NF97U135V5D	97%	2-Stage	Variable Speed	132/126K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 24.5 x 28.5	176.70
	NF97X040V3B	97%	2-Stage	Variable Speed	40/39K	3	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 17.5 x 28.5	118.75
	NF97X060V3B	97%	2-Stage	Variable Speed	60/58K	3	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 17.5 x 28.5	123.50
	NF97X080V4C	97%	2-Stage	Variable Speed	80/78K	4	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 21 x 28.5	146.30
	NF97X080V5C	97%	2-Stage	Variable Speed	80/78K	5	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 21 x 28.5	148.20
NEW	NF97D070V4B	97%	2-Stage	Variable Speed	66/64K	4	Downflow	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF97D090V5C	97%	2-Stage	Variable Speed	88/85K	5	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	157.70
	NF97D110V5C	97%	2-Stage	Variable Speed	110/106K	5	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	165.30
	NF96U045V3B	96%	2-Stage	Variable Speed	44/42K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF96U070V3B	96%	2-Stage	Variable Speed	66/62K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF96U090V3C	96%	2-Stage	Variable Speed	88/84K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	145.35
	NF96U090V5C	96%	2-Stage	Variable Speed	88/85K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	156.75
	NF96U110V5C	96%	2-Stage	Variable Speed	110/106K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	166.25
	NF96U135V5D	96%	2-Stage	Variable Speed	132/126K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 24.5 x 28.5	176.70
	NF96D070V4B	96%	2-Stage	Variable Speed	66/64K	4	Downflow	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	142.50
	NF96D090V5C	96%	2-Stage	Variable Speed	88/85K	5	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	157.70
	NF96D110V5C	96%	2-Stage	Variable Speed	110/106K	5	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	165.30

Note: Maximum efficiency and capacity performance ratings shown. Actual performance may vary by equipment matchup selection.

NF96/95****S Single Stage Gas Furnaces

	Model	Efficiency (% AFUE)	Stages	Motor	AHRI Rated BTH/hr Input/Output	Cooling (Nominal Tonnage)	Air flow	Emissions	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
	NF96U045S3B	96%	Single-Stage	Constant Torque	44/43K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	113.05
	NF96U070S3B	96%	Single-Stage	Constant Torque	66/64K	3	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	120.65
	NF96U090S4C	96%	Single-Stage	Constant Torque	88/86K	4	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	140.60
	NF96U110S5C	96%	Single-Stage	Constant Torque	110/107K	5	Upflow/Horizontal	Low NOX (<40 Ng./J)	33 x 21 x 28.5	151.05
	NF96D045S3B	96%	Single-Stage	Constant Torque	44/43K	3	Downflow	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	113.05
	NF96D070S4B	96%	Single-Stage	Constant Torque	66/64K	4	Downflow	Low NOX (<40 Ng./J)	33 x 17.5 x 28.5	127.30
	NF96D090S4C	96%	Single-Stage	Constant Torque	88/86K	4	Downflow	Low NOX (<40 Ng./J)	33 x 21 x 28.5	142.50
	NF95X040S3B	95%	Single-Stage	Constant Torque	40/39K	3	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 17.5 x 28.5	115.90
	NF95X060S3B	95%	Single-Stage	Constant Torque	60/58K	3	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 17.5 x 28.5	121.60
	NF95X080S4C	95%	Single-Stage	Constant Torque	80/78K	4	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 21 x 28.5	140.60
	NF95X100S5C	95%	Single-Stage	Constant Torque	100/97K	5	Upflow/Horizontal	Ultra Low Nox (14 Ng./J)	33 x 21 x 28.5	149.15

Note: Maximum efficiency and capacity performance ratings shown. Actual performance may vary by equipment matchup selection.

* Unit height excludes flange