



## Packaged Terminal Air Conditioners

Uncompromising reliability from the brand you trust

**Hotpoint**<sup>®</sup>

A man with a beard, wearing a dark suit and a white shirt, is sitting on a bed. He is smiling and looking towards the right. He is holding a tablet computer in his hands. The bed has white linens and a green pillow. The background is a blurred window with grey curtains.

# Hotpoint®

## A History of Dependability

Founded in 1903, Hotpoint prides itself in creating products that make comfort affordable. Whether it's with a revolutionary redesign of the iron or the first electric range cooktop, we have always honored our customers' need for products that make everyday life easier, all at a price they could afford.

Today, Hotpoint continues that legacy with Packaged Terminal Air Conditioners that lead the way in durability, affordability and ease of use and installation. Because your guests' comfort and your success matter to us.

# Hotpoint® Packaged Terminal Air Conditioners

## Air Conditioner with Electric Heat

| MODEL | AH11E07D3B | AH11E09D3B | AH11E12D3B | AH11E15D3B |
|-------|------------|------------|------------|------------|
| BTU   | 7,000      | 9,000      | 12,000     | 15,000     |
| EER   | 11.9       | 11.3       | 10.7       | 9.7        |
| VOLTS | 230/208    | 230/208    | 230/208    | 230/208    |

## Air Conditioner/Heat Pump with Backup Electric Heat

| MODEL | AH11H07D3B | AH11H09D3B | AH11H12D3B | AH11H15D3B |
|-------|------------|------------|------------|------------|
| BTU   | 7,000      | 9,000      | 12,000     | 15,000     |
| EER   | 11.9       | 11.4       | 10.5       | 9.7        |
| COP   | 3.4        | 3.4        | 3.2        | 3.0        |
| VOLTS | 230/208    | 230/208    | 230/208    | 230/208    |



# Performance & Reliability Features

Backed by an Industry Leader

## 3-Speed Fan

Give guests control over their comfort with three fan speeds to choose from.

## 4-Temperature Limiting Options

Easily select one of four temperature ranges for peak efficiency and total customer comfort.

## Intuitive Display

Allow guests to easily customize their preferred settings and reduce maintenance calls with an easy-to-use control panel.

## Power Cord (LCDI) Included

Hotpoint PTACs come with everything needed for a quick and easy installation.

## Automatic Emergency Heat

Keep guests comfortable with a heating option that uses electric resistance heat in heat-pump mode.

## Freeze and Frost Protection

Automatic freeze and indoor frost control keep units operating in peak condition.

## Auto Power Recovery

In case of power failures, units automatically resume their operation when power restores, reducing maintenance calls.

## Self-Diagnostics

Quickly and easily identify service needs with a nine-point diagnostic code system.

**1** -Year Full Parts and Labor Warranty

**5** -Year Limited Warranty

### Additional Features

**Remote thermostat compatibility**

**Works with central desk control systems**

**Energy-efficient heat pump models available**

**Tangential fan for smooth air flow and sound**

**Heat pump models include staged heating**

**Removable filters for easy maintenance**

With a long history of creating durable products at an affordable price, Hotpoint is your trusted PTAC brand.



**Chassis**

**Wall Case**  
(Sold Separately)

**Front Panel**

**Grille**  
(Sold Separately)

## Built to Withstand the Elements

No matter how it feels outside, Hotpoint PTACs are engineered with durable materials to provide unwavering comfort inside.

See more at [Hotpoint.com](https://www.hotpoint.com)

# Hotpoint PTAC Nomenclature

|                                  |  |          |          |   |          |          |  |          |          |
|----------------------------------|--|----------|----------|---|----------|----------|--|----------|----------|
| <b>A</b>                         | <b>H</b>   | <b>1</b> | <b>1</b> | <b>H</b>  | <b>0</b> | <b>9</b> | <b>D</b>   | <b>3</b> | <b>B</b> |
| <b>Brand</b><br>H=Hotpoint® PTAC | <b>Unit Series</b><br>Chassis series   |          |          | <b>Nominal Cooling Capacity</b><br>07=7,000 BTUH cooling<br>09=9,000 BTUH cooling<br>12=12,000 BTUH cooling<br>15=15,000 BTUH cooling |          |          | <b>Heater Watts/Amps</b><br>2=2.4 kW; 15 amp<br>3=3.4 kW; 20 amp<br>5=5.0 kW; 30 amp |          |          |
|                                  | <b>Unit Type</b><br>E=cooling with electric resistance heat<br>H=cooling/heat pump with backup electric heat |          |          | <b>Voltage/Phase/Frequency</b><br>D=230/208 volt, single phase, 60 Hz<br>E=265 volt, single phase, 60 Hz                              |          |          | <b>Special Features</b><br>B=base unit   |          |          |

## Product Specifications

| Hotpoint Heat/Cool Series                         | Air Conditioner with Electric Heat            |   |   |   | Air Conditioner/Heat Pump with Backup Electric Heat |   |   |   |
|---|---|---|---|---|---|---|---|---|
|   | AH11E07D3B                                    | AH11E09D3B                                    | AH11E12D3B                                    | AH11E15D3B                                    | AH11H07D3B  | AH11H09D3B                                    | AH11H12D3B                                    | AH11H15D3B                                    |
| <b>Voltage</b>                                    | 230/208                                       | 230/208                                       | 230/208                                       | 230/208                                       | 230/208   | 230/208                                       | 230/208                                       | 230/208                                       |
| <b>Cooling Capacity</b>                           |   |   |   |   |   |   |   |   |
| Cooling BTUH                                      | 7300/7100                                     | 9200/9000                                     | 12000/11800                                   | 14700/14500                                   | 7200/6800   | 9000/8800                                     | 12000/11800                                   | 14700/14500                                   |
| EER (BTU/Watt)                                    | 11.9  | 11.3  | 10.7  | 9.7   | 11.9  | 11.4  | 10.5  | 9.7   |
| COP   |   |   |   |   | 3.4   | 3.4   | 3.2   | 3.0   |
| <b>Features</b>                                   |   |   |   |   |   |   |   |   |
| Refrigerant Type                                  | R-410A  | R-410A  | R-410A  | R-410A  | R-410A  | R-410A  | R-410A  | R-410A  |
| Electronic Controls                               | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| LCDI Power Cord                                   | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Remote Thermostat Capable                         | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Slide-In Chassis                                  | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Discharge Grille                                  | 1-position                                    | 1-position                                    | 1-position                                    | 1-position                                    | 1-position  | 1-position                                    | 1-position                                    | 1-position                                    |
| Fan Motor   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |
| Fan Speeds  | 3   | 3   | 3   | 3   | 3   | 3   | 3   | 3   |
| Heat - Cool                                       | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| Rotary Compressor                                 | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| Fan Cycle Control                                 | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Freeze Control                                    | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Automatic Indoor Frost Control                    | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Heat pump with Resistance Heat Backup             |   |   |   |   | ●   | ●   | ●   | ●   |
| Automatic Emergency Heat                          |   |   |   |   | ●   | ●   | ●   | ●   |
| Auto Power Recovery                               | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Central Desk Control Capable                      | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| Fresh Air Vent                                    | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter       | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter | Concealed Manual Vent Control Vent Air Filter |
| Outdoor Vent / Exhaust                            | ●   | ●   | ●   | ●   | ●   | ●   | ●   | ●   |
| <b>Weight &amp; Dimensions</b>                    |   |   |   |   |   |   |   |   |
| Overall Dimensions (including room cover) (WxHxD) | 42 x 16 x 21                                  |   |   |   | 42 x 16 x 21  |   |   |   |
| Net Weight  | 99 lb   | 105 lb  | 112 lb  | 113 lb  | 101 lb  | 107 lb  | 116 lb  | 116 lb  |
| Approximate Shipping Weight                       | 124 lb  | 130 lb  | 136 lb  | 137 lb  | 127 lb  | 132 lb  | 140 lb  | 141 lb  |

### Accessories to add

| Model # | Description        |
|---------|--------------------|
| RAB80   | Hotpoint Wall Case |
| RAG70   | Hotpoint Grille    |
| RAA70   | Hotpoint Filter    |



**Hotpoint Wall Case**  
RAB80



**Hotpoint Grille**  
RAG70



**Hotpoint Filter**  
RAA70