

Eterna[™] Series

Spring 2006



Introduction



GE Eterna™ Series is the smart choice for your kitchen or laundry room, offering you a remarkable array of innovative features and a fresh, contemporary look you'll love. The Eterna Series offers great value, too – the perfect combination of must-have features, reliable performance and affordable price.

Eterna Series appliances are available only from selected dealers. Talk to yours – and look through the following pages – and you're sure to find Eterna models that fit your needs, your family's lifestyle and your budget perfectly. And remember, with Eterna, you're choosing America's #1 Preferred Appliance Brand,* GE Appliances.

Before purchasing any appliance, read important information about its estimated annual energy consumption or energy efficiency rating that is available from your retailer or at ge.com.

*GE is the appliance brand most often mentioned among the brands rated as offering the best products and services in America, according to a recent Louis Harris Poll 2004.

Contents



3 Side-by-side refrigerators 7 Specifications & installation



4 Electric range 8 Specifications & installation



4 Gas range 9 Specifications & installation



Microwave oven
9
Specifications
& installation



5 Dishwashers 10 Specifications & installation



6 Washers 11 Specifications & installation



6
Dryers
11
Specifications & installation

GE Eterna Refrigerators



External controls with actual temperature display eliminate guesswork in setting refrigerator temperatures.



Integrated Ice System pulls out and down, providing easy access to cubed ice.



TurboCool setting Quickly cools the refrigerator after frequent door openings or when hot items are placed inside.



Freshness Center maximizes shelf space and enhances interior appearance.



GE SmartWater™ Plus filtration system delivers clean, greattasting water and ice through the LightTouch! dispenser with indicator light.





ESS25KST

25.4 cu. ft. side-by-side refrigerator

- Contoured doors
- External controls with actual temperature display, Quick Ice™, child lock and door alarm
- Freshness Center[™]
- TurboCool[™] setting
- Integrated Ice™ system
- Tilt-out freezer door bins
- Slide-out freezer baskets
- Dimensions (HxWxD) 69-1/4" x 35-3/4" x 33-3/4"





ESC23KST

22.7 cu. ft. CustomStyle[™] side-by-side refrigerator

- External controls with actual temperature display,
 Quick Ice, child lock and door alarm
- Freshness Center
- TurboCool setting
- Integrated Ice system
- Tilt-out freezer door bins
- Slide-out freezer baskets
- QuickSpace[™] shelf
- Dimensions (HxWxD) 69-1/4" x 32-3/4" x 33-9/16"



ESC23KSTSS

ECF23KGTWW high-gloss doors



ECF23KGTBB high-gloss doors

GE *Eterna*[™] ranges



5.3 cu. ft. oven capacity provides an impressively large oven interior for cooking more dishes and large meals at one time.



TrueTemp system delivers even heat distribution and maximum oven control.



Fifth element keeps food warm and ready to serve



EER3001K 5.3 cu. ft. electric range

- Self-clean oven
- TrueTemp[™] system
- Fifth element
- 9"/12" dual element
- Heavy-duty self-clean oven racks
- Drawer liner
- Dimensions (HxWxD) 46-7/8" x 30" x 29"





TrueTemp system delivers even heat distribution and maximum oven control.



PowerBoil™ 15,000 BTU burner provide powerful burner output for efficient heat-up and boiling.




Precise simmer burner allows for low even heat distribution for delicate foods and sauces.



EGR3001EJExtra-large capacity gas range

- TrueTemp[™] system
- QuickSet IV oven controls
- Precise simmer burner
- Medium cast grates
- Drawer liner
- Dimensions (HxWxD) 47-1/2" x 30" x 29"



GE Eterna over-the-range microwave oven



Sensor cooking controls automatically adjust time and power for delicious cooking results.



Turntable on/off is ideal for oversized dishes that are larger than the diameter of the turntable.




*IEC test procedure

EMO3000HSS

1.6 cu. ft. capacity/1000 powerful watts*

- Sensor cooking controls
- Turntable On/Off
- Auto and time defrost
- Three-speed, 300-CFM venting system
- Dimensions (HxWxD) 16-13/32" x 29-7/8" x 15-1/14"



GE Eterna Built-in dishwasher



Giant tub with maximum capacity **Duron racking** washes up to 16 place settings at once.



OuietPower™3 reduces ambient sound by keeping noise from escaping during wash cycle.



SUSTAINED EXCELLENCE

EDW6060L

Giant Tub with Maximum Capacity Duron[™] Racking

- Two Utility Shelves in Tiered Upper Rack with StemSafe[™], Silver
- 6-Level BrilliantĆlean™ Wash System with CleanSensor™
- Light-Touch Electronic Controls with 6 Cycles/3 Options
- SpeedCycle
- Dimensions (HxWxD) 33-3/4" x 24" x 25"



EDW6060LSS

EDW6000LWW



EDW6000LBB



Countdown display with 1-9 hour **Delay Start** signals remaining cycle time and makes it easier than ever to wash dishes at any hour.



QuietPower² sound package softens the sound of the dishwasher for a more peaceful kitchen.



SaniWash™ cycle NSF - certified to sanitize dishes.





EDW5060LSS

Giant Tub with Super Capacity Racking

- Two Utility Shelves in Tiered Upper Rack with StemSafe[™], Silver
- SaniSensor[™]
- Electronic Controls with 6 Cycles/4 Options
- QuietPower^{™2} Sound Package
- Dimensions (HxWxD) 33-3/4" x 24" x 25"



EDW5060LSS



EDW5000LWW



EDW5000LCC



EDW5000LBB

GE Eterna™ washers and dryers



Stainless steel basket resists rust, won't chip or peel.



PerfecTemp regulates wash water temperatures for proper fabric care.



Handwash cycle provides effective yet gentle cleaning action for delicate fabrics.

EWA6500D

3.5 cu. ft. King-size capacity washer

- Stainless steel basket
- 26 wash cycles
- 6 wash/spin speeds
- Light cycle
- Spot sprau
- Handwash cycle
- PerfecTemp
- Four water levels
- Bleach and fabric softener dispensers
- Dimensions (HxWxD)
 42" x 27" x 25-1/2"



EWA6500DWW



Stainless steel drum resists rust, won't chip or peel.



Sensor Dry Plus continually monitors moisture levels to help clothes look better, longer.



Interior dryer light lets you see everything inside for easy loading and unloading.





EED6500D

7.0 cu. ft. super capacity dryer

- Sensor Dry Plus
- Stainless steel drum
- Deluxe end-of-cycle signal
- Four heat selections

EED6500DWW

electric dryer

- Wrinkle Care Extended Tumble
- Ten dry cycles
- Dimensions (HxWxD) 42" x 27" x 28-1/4"



EGD6500DWW gas dryer






EWA4500D

3.2 cu. ft. King-size capacity washer

- ExtrAction™ Basket
- Rotary electronic controls with cycle status light
- 5 wash speeds
- 24 wash cycles
- Light cycle
- Extended spin
- Bleach and fabric softener dispensers
- Four water levels
- Dimensions (HxWxD) 42" x 27" x 25-1/2"



EWA4500DWW





EED4500D

7.0 cu. ft. super capacity dryer

- Quick Fluff
- Auto Dry
- Four heat selections
- Six dry cycles
- Quiet-By-Design™
- EED4500DWW electric dryer
- Fixed End-Of-Cycle Signal
- Dimensions (HxWxD) 42" x 27" x 25-1/2"



GE Eterna side-by-side refrigerators

	ESS25KST ESF25KGT	ESC23KST ECF23KGT
Stainless steel model	•/-	•/-
CustomStyle™ configuration		•
Capacity		
Total (cu. ft.)	25.4	22.7
Fresh food (cu. ft.)	15.91	14.38
Freezer (cu. ft.)	9.48	8.23
Shelf area (sq. ft.)	22.6	18.5
Fresh food features		
Multi-flow air system	•	•
Electronic sensors	Divis	DI
SmartWater™ filtration system	Plus	Plus
LightTouch! dispenser features	Crushed ice, cubes, water	Crushed ice, cubes, water
Light and child lock Door alarm	•	•
Ouick Ice™ feature	•	•
Water filter indicator light	•	•
Actual temperature display	•	•
External controls	•	•
TurboCool™ setting	•	•
Cabinet shelves	3 glass	3 glass
Adjustable	3	3
Slide-out, spillproof	3	3
QuickSpace™ shelf	<u> </u>	•
Integrated shelf support system	•	•
Snugger™ clip	1	1
Freshness Center™	•	•
Deli drawer	1 adj. humidity	1 adj. humidity
Vegetable/fruit crisper	1 adj. humidity	1 adj. humidity
Sealed pan	1 adj. humidity	1 adj. humidity
ClearLook™ door bins	4 (2 adj. with gallon storage)	4 (3 adj.)
Dairy compartment	• • • • • • • • • • • • • • • • • • •	- (5 ddj.)
Interior light system	Dual-level	Dual-level
Quiet design	Deluxe	Deluxe
AutoEnergy saver	•	•
NeverClean™ condenser	•	•
ENERGY STAR®	•	
Freezer features		
Integrated Ice™ system	•	•
FrostGuard™ technology	•	•
Wire cabinet shelves	2	2
Storage basket(s)	3 slide-out	3 slide-out
Door shelves	3 (2 tilt-out)	3 (2 tilt-out)
Interior light	•	•
Appearance		
	<u>ss</u>	<u>SS</u>
Color(s) available*	WW, CC, BB	WW, BB
CustomStyle configuration	_	Trimless
	Stainless steel tubular	Stainless steel tubular
Deluxe door handle(s)*	CM CleanTouch	CM CleanTouch
		Rounded doors
Exterior design	Contoured doors	High-gloss rounded doors
Exterior design	High-gloss cont. doors Case only (black)	Case only (black)
Textured steel door and case	<u>case only (black)</u>	<u>Case Only (black)</u>
Stain. steel side panel accessory (opt.)	•/-	
Adjustable rollers	Front	Front
Weights & Dimensions		110110
Height to top of hinge (in.) A	69-1/4	69-1/4
Height to top of case (in.) B	68-3/4	68-3/4
Case depth without door (in.) C†	28	23-7/8
Case depth less door handle (in.) D†	31-1/4	26-3/4
Case depth with door handle (in.) E†	33-9/16	29-3/16
Depth w/fresh food door open 90° (in.) F†	50-1/16	45-9/16
Width (in.) G	35-3/4	35-3/4
Width w/door open 90° with	22.37.	41-3/16
door handle (in.) H	41-3/16	40-3/4
Each side (in.)		1/8
EUCH Side (III.)	1/8	
Top (in.)	1/8	1
		1 1/2
Top (in.)	1	


*Color(s) available: SS = Stainless steel, WW = White, CC = Bisque,
BB= Black, CM = Color-Matched.
†Water hook-up fits in back air clearance when calculating installation depth.
If installed against a wall, allow clearance of 10-3/4" on 20 cu. ft. and 22 cu. ft.
models; 14-3/16" on 25 cu. ft. models on freezer side to remove bin. Clearances
required to remove fresh food full-size pan without disassembling: 13-1/2" on 20
cu. ft.; 15" on 22 cu. ft.; and 18-15/16" on 25 cu. ft. Allow additional space for any
necessary levelina addistments.

necessary leveling adjustments.
ALL MODELS AVAILABLE IN U.S. AND CANADA.





Side-by-side refrigerators



GE *Eterna*™ electric ranges

	EER3001KSS EER3000KTW EER3000KKC EER3000KBB
Features	
Self-clean oven	•
Self-clean latch	•
Oven capacity (cu. ft.) (upper/lower)	5.3
Self-clean oven racks	2
-	True white
Ceramic-glass cooktop	<u>True bisque</u> Black
One-piece upswept cooktop	Blück ●
9"/12" dual element	1 (3000W)
8" ribbon heating element	1 (2000W)
6" ribbon heating element	2 (1500W)
Infinite heat controls	•
TrueTemp™ system	
Six-pass power bake element	0 : 10 : 11
QuickSet oven controls	QuickSet IV
Digital temperature display	•
Delay bake	•
Oven light pad	_
Self-clean cool-down time display	•
Delay clean option	
Auto oven shut-off	w/override
Certified Sabbath mode	•
Audible preheat signal	•
Dual element bake	•
Hot surface lights	_
Interior oven light	Pad
Storage drawer	•
Drawer liner	•
Broiler pan with grid	•
Appearance	
Color appearance*	<u>SS</u> TW/KC/BB
	Stainless steel
	White
	Bisque
Frameless glass oven door	Black
Oven door with window	Big hearth
Designer-style handle	•
Weights & Dimensions	
Overall oven interior dimensions	
(WxHxD in inches)	24-1/8 × 19-1/2 × 19-3/8
Approx. shipping wt. (lbs.)	181
Power/Ratings	
KW rating @ 240V	12.0
208V	9.0
Amp rating @ 240V / 208V	40
*SS = Stainless steel with black accents	, TW = True white glass

^{*}SS = Stainless steel with black accents, TW = True white glass door, KC = Bisque with bisque glass door, BB = Black with black glass door.

All ranges are shipped with cooktop cleaning creme & pad.

Note: Conforms to U.L. requirements for 0" spacing for adjacent walls below countertops. To reduce possibility of scorching of walls, it is recommended a minimum of 1-1/2" spacing be allowed from adjacent side walls to allow for possible extended, high-heat, no-load heating element operation.

Receptacle locations: For 30" Free-Standing Ranges locally approved flexible service cord or conduit must be used because terminals are not accessible after range installation. See shaded area drawing for location of electrical outlet box. Recommended outlet locations allow range to be installed directly against wall.







All GE ranges are equipped with an Anti-Tip device. The installation of this device is an important, required step in the installation of the range.

Electric free-standing range Anti-tip bracket (Part No. 164D3799P002) JB988/968/910/900, JBP84/81/80/72/70/66/ 65/64/49/35/27/24/22 and JBS55

Anti-tip bracket (Part No. 183D6270P001) JBS27/07/15/03 and JBP21/15

Dimensions (in inches)

Model	Α	В	C*	D
EER3001K	29-7/8	46-7/8	25-3/8	47-5/8
EER3000K	29-7/8	46-7/8	25-3/8	47-5/8

*Dimension from wall to front of closed oven door handle is 27-3/8" on models JB988/968/ 910/900 and 27-3/4" on models JB948/18/80/ 72/70/66/65/64/49/35/27/24 and JBS55.

Installation information
(in inches)

Acceptable electrical outlet area

29-7/8

*Dimension from wall to front of closed oven door handle is 27-3/4

GE Eterna gas ranges

	Sealed burner models
	EGR3001EJSS EGR3000EJWW EGR3000EJCC EGR3000EJBB
Capacity	
Extra-large 4.8 cu. ft. oven	•
Features	
Oven cleaning	Self-clean
Deep recessed porc.	_
cooktop	0 1 1
Cooktop burners Precise Simmer burner	Sealed (1) 5.000 BTU
(Nat.)	140° Simmer
(NUC.)	(1) 15,000 BTU,
All-purpose burners	(1) 11,000 BTU,
(Nat.)	(1) 9,500 BTU
Valves (degree of turn)	270
TrueTemp™ system	•
Electronic controls	•
QuickSet oven controls	QuickSet IV
Auto self-Clean	•
Electronic clock and timer	•
Automatic oven timer	•
Audible preheat signal	•
Auto oven shut-off	•
Certified Sabbath mode	•
One-piece upswept cooktop	Porcenam.
	Matte black medcast
	Grey medium-cast
Removable grates	Black medium-cast
Continuous grates	Dishwasher-safe
Ignition system	Electronic
Oven racks Six embossed rack positions	2 self-clean
Broiler pan	
Scratch-resistant backguard	Porcenam.
Interior oven light	Forcendin.
Storage drawer	•
Drawer liner	•
In-oven broiling	•
Appearance	
r.ppeulunes	SS
Color appearance*	WW/CC/BB
	Stainless steel
	White glass
Frameless oven door	Black glass
Oven door with window	Big ClearView™
Designer-style handle	•
Weights & Dimensions	
Overall oven interior dimen.	
(WxHxD in inches)	24 x 18-1/2 x 19
Approx. shipping wt. (lbs.)	210
Power/Ratings	(4) 45 0 /44 0
Tan burnara	(1) 15.0/11.0
Top burners (000's BTUs) Nat/LP	(1) 5.0/5.0 (2) 9.1/9.1
Oven/broiler burners	16.0/16.0 Oven
(000's BTUs) Nat/LP	12.5/12.0 Broil
Gas range electrical rating	120V, 60Hz, 5A
LP conversion kit (included)	120V, 00112, JA
*CC Chairless should the blank	

**SS = Stainless steel with black accents, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with block glass door, Factory set for Natural Gas. A set of LP orifices is included with each range for LP conversion.








All GE ranges are equipped with an Anti-Tip device. The installation of this device is an important, required step in the installation of the range.


Dimensions (in inches)

Model	Α	В	C*	D
EGR3001	30	47-1/2	26-1/4	46-3/8
EGR3000	30	47-1/2	26-1/4	46-3/8
*Di	Cara and	4 - E 4 - A	alasa alab	

*Dimensions from wall to front of closed door handle is 29".

Installation information (in inches)






GE Eterna over-the-range microwave one

		EMO3000HSS EMO3000HWW EMO3000HCC EMO3000HBB
Capacity		
Oven cavity (cu.	ft.)	1.6
Features		
Watts (IEC-705 t	est procedure)	1000
Electronic touch		•
SmartControl su		
w/interactive di		•
Scrolling displo		1-line
Clock and AM/		•
Variable scroll		•
Help pad		•
Concurrent pro	parammina	•
Sensor	Beverage	•
controls	Popcorn	•
	Potatoes	•
	Reheat	•
	Vegetables	•
Express Cook (1-		•
Instant On conti		•
Time cook	UIS	18.11
Add 30 Seconds		10.11
Auto/Time Defro		•/•
Power levels	JSL	10
Delay Start/Ren	-:	10
		Cine Alleria
Cooking system	1	CircuWave
Turntable	Tr.	
Turntable On/Ot	T	•
Interior lighting	P. L.C.	•
Full-view cookto	p lighting	•
Night light		•
Programmable	night light	•
Timer On/Off		
Cooking comple	ete reminder	•
Child lockout		•
300-CFM exhau	st fan	2-speed
Appearance		
Color appearan	ce*	SS/WW/CC/BB
		Black/White/
Case color		Bisque/Black
Weights & Dir		
	erior dimensions	20-1/4 x
WxHxD (in inche		9-1/4 x 14-13/32
Approx. shippin	g weight (lbs.)	67
Power/Rating		
Input Volt/Hertz	:	120V/60Hz
Input Amps/Wa		15A/1.58KW
Accessories		
Cooking guide le	nhel	•
Oven rack(s)	abci	1 (2-positions)
	arcoal filter kit (opt.)	JX81A
		JX81A JX48BL/WH
Filler panel kit (a	pt.1	JX48BL/VVH
Warranty		
*SS = Stainless s	ar in-home warranty** steel, WW = White on wh	ite, CC = Bisque on bisque

Overall exterior dimensions (in inches) Model W D EMO3000H 29-7/8 15-1/4

NOTE: Convenience popcorn pad designed for use with 3 package sizes—3.5, 3.0 and 1.75 oz.

This information is not intended to be used for installing unit described. Before installing, consult installation instructions packed with product/kit for current dimensional data



BB = Black on black.
**See warranty for details.


GE *Eterna*™ dishwashers

	ENERGY STAR
	EDW6060LSS
	EDW6000LWW EDW6000LCC
	EDW6000LCC EDW6000LBB
Features	
Tub and door liner	PermaTuf®
Giant tub	•
Front appearance	Flat door
Full-length door design	•
Wash system	BrilliantClean™
Wash arms Wash levels	3 direct-feed
washievels	6-towerless 100% triple with
Water filtration	ExtraFine™ filter
Dual pumps and motors	•
Hard food disposer	Piranha™
Sensor	CleanSensor
Automatic	
temperature control	
Dince aid dispenser	w/indicator
Rinse aid dispenser Electronic controls	& adjustment Light-touch
Electronic controls	Countdown display with
Cycle progress indicators	4 status lights
Touchpads	9
Cycles/Options	6/3
Last cycle memory	•
Cycles	
Anti-bacteria (NSF*)	•
Pots & Pans	-
Normal Wash China/Crystal	•
SpeedCycle (wash & dry)	•
Rinse Only	•
Options	
Delay Start	1-9-hour
Hi-Temp Wash	ExtraHot Wash
Added Heat	•
Hi-Temp Rinse	Auto w/ExtraHot Wash
Heated Dry HotStart	Automatic
Child lock	Automatic
Racking	· · · · · · · · · · · · · · · · · · ·
Maximum capacity racking	Duron
Upper rack	Deep-tiered
Lower rack	Towerless
Utility shelves	2 upper
	Maximum capacity
Silverware basket	3-pc. w/3 silver cell covers
Hard countertop installation	GPF65
Low profile installation Latch	Caucago
DryIndex	Squeeze
Calrod heating element	Multi-wattage
Convection airflow	• •
Quiet	
Sound insulation package	QuietPower ³
Tub insulation	Full wrap blanket
Door insulation	Mastic and sound coat
QuietPower motor	•
Appearance	
Colors available**	SS/WW/CC/BB
Weights & Dimensions	7.
Height w/legs retracted (in.)	34 33-5/16
Height w/legs removed (in.)	
Overall width (in.) Overall depth (in.)	24 25 max.
Approx. shipping weight (lbs.)	100
Accessories	230
1/4" panel kit	GPF525W/C/B
3/4" panel kit *Certified by National Sanitation Fo	GPF575

^{*}Certified by National Sanitation Foundation.

**SS = Stainless steel, WW = White on white, CC = Bisque on bisque,
BB = Black on black.

Dimensions (in inches)



Flectrical rating

Electrical rating
Voltage AC120
Hertz60
Total connected load amperage9.1* Calrod heater watts875
*EDW6000 series total connected load amperage10
For use on adequately wired 120V, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be grounded for safe operation.


	ENERGY STAR EDW5060LSS EDW5000LWW EDW5000LCC EDW5000LBB
Features	
Tub and door liner	PermaTuf
Giant tub	•
Front appearance	Flat door
Full-length door design	•
Wash system	BrilliantClean
Wash arms	3 direct-feed
Wash levels	6-towerless
and the state of	40004 1 1 15 1 5 1 5 1
Water filtration	100% triple w/ExtraFine filter
Dual pumps and motors	Diameter.
Hard food disposer	Piranha
Sensor	SaniSensor™
Automatic temperature control	
	w/indicator and
Rinse aid dispenser	adjustment
Control type	Electronic
Cycle progress indicators	Countdown display with 4 status lights
Touchpads	11
Cycles/Options	6/4
Last cycle memory	•
Cycles	
SaniWash (NSF*)	•
Pots & Pans	•
Normal Wash	•
Light Wash	•
China/Crystal	•
Rinse Only	•
Options	
Delay Start	2/4/8-hour
Heated Dry	•
HotStart™	•
Hot prewash	•
Child lock	•
Racking	Tall-over-tall™
Upper rack	Tiered
Lower rack	Towerless
LIMPS In a large	2 plastic with
Utility shelves	2 StemSafe silver
Silverware basket	Super capacity 1-pc. w/3 silver cell covers
Hard countertop installation	GPF65
Low profile installation	•
Latch	Squeeze
DryIndex	Squeeze
Calrod® heating element	Multi-wattage
Quiet	r-iditi-wattage
Sound insulation package	QuietPower ²
Tub insulation	Full wrap blanket
Active vent system	• an an ap blurinet
QuietPower™ motor	•
Appearance	
Colors available**	SS, WW, CC, BB
Weights & Dimensions	22,
Height w/legs retracted (in.)	34
Height w/legs removed (in.)	33-5/16
Overall width (in.)	24
Overall depth (in.)	25 max.
Approx. ship. weight (lbs.)	100
Accessories	100
1/4" panel kit	GPF525W/C/B
3/4" panel kit	GPF575
The state of the s	

All GE Eterna dishwashers are equipped with the following: 120% inlet water capacity and leveling screws.

*Certified by National Saritation Foundation.

**SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

Dishwasher dimensions (in inches)



Electrical rating

voitage AC1	_(
Hertz	50
Total connected load amperage	10
Calrod heater watts72	25
For use an adequately wired 120V	


For use on adequately wired 120V, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be rounded for safe operation.




GE Eterna washers

	EWA6500D	EWA4500D
Capacity		
Capacity cu. ft.	3.5 king-size	3.2 super plus
Controls		
Rotary electronic	•	•
Status indicators	Status lights	Status lights
Water temp system	PerfecTemp	PerfecTemp
Wash/rinse temps	3	3
Water levels	4	4
Spot spray	•	
Wash system		
Wash basket	Stainless steel	ExtrAction™
	GentlePower	GentlePower
Wash mechanism	agitator	agitator
Wash/spin combinations	6	5
Drive system		
Transmission	Steel	Steel
Maximum spin speed	630 RPM	630 RPM
Dispensers		
Bleach	•	•
Fabric softener	•	•
Wash cycles		
	26	24
Number of cycles	26	24
Cottons Regular	•	•
Extra heavy soil		•
Heavy soil		•
Medium soil	_	•
Light soil	•	•
Easy Care	•	•
Auto soak (15 min.)	•	•
Heavy soil		_
Medium soil	•	•
Light soil	•	•
Casuals - Pulsed	•	•
Heavy soil	•	•
Medium soil	•	•
Light soil	•	•
Delicate	•	•
Medium soil	•	•
Light soil	•	•
Handwash - Pulsed	•	
Hang to Dry/Prewash	•	•
Special Cycles		
2nd rinse	•	•
Soak option	•	
Extended spin	•	•
Rinse & spin (Quick rinse)	•	•
Spin only	•	•
Additional Features		<u> </u>
- Laure Original Caracia	Quiet-By-	Quiet-By-
Quiet performance	Design	Design
Color lid instructions	Design	Design
	_	
Appearance	14/14/	14/14/
Colors available*	WW	ww
Weights & Dimensions	475	450
Approx. shipping wt. (lbs.)	175	160

Washer dimensions (in inches)





Washer specifications

Circuit requirements:

An individual, properly grounded branch circuit, with a three-prong grounding-type receptacle, protected by a 15- or 20-amp circuit breaker or time-delay fuse is required.

Electrical rating: 115V, 60Hz, 10A

Washer note:

Washer wall outlet must be located within 36" of service cord entry. Wall outlet must not be located behind dryer.

GE Eterna dryers

Electric	EED6500D	EED4500D
Gas	EGD6500D	EGD4500D
Capacity		
Capacity cu. ft.	7.0 Super	7.0 Super
Controls		
Rotary	•	•
Heat selections	4	4
Dry system		
Temperature sensor	Sensor Dry	Thermostat
Dryer drum	Stainless Steel	DuraDrum
Drum baffles	White	White
Signals		
End-of-cycle	Deluxe	Fixed
Dry cycles		
Number of cycles	10	6
Cottons	•	•
Easy care	•	•
Optional wrinkle care		•
Damp dry	•	•
Time control	80 min.	80 min.
Special cycles		
Dewrinkle	•	•
Quick Fluff (no heat)	•	•
Additional features		
Quiet performance	Quiet-by-Design	Quiet-by-Design
Deluxe dryer rack		
Dryer interior light	•	•
Appearance		
Colors available*	WW	WW
Weights & dimensions		
Approx. shipping weight- electric (lbs.)	119	119
Approx. shipping weight- gas (lbs.)	125	125
-	•	


*WW = White on white

В

7.0 cu. ft. capacity

Dryer dimensions (in inches)

Side View



Rear View

Power cord locations 7.0 cu. ft. dryers

Back View

27		. 5"	
25-1/2*			
42			
28-1/4			
23-1/2			
11-1/2	Power		
3 - 1/2	Cord Hole		
2			
2-1/2	-	4'	4-1/2'
36		Д	<u> </u>
8-1/2	Back V	OW	

*24-1/2" from the edge of the side panel to the front. 25-1/2" from front to edge of end caps.

Dryer specifications

Exhaust options:

Electric: 4-way via rear, right, left and bottom. Gas: For 5.8, 6.0 and 7.0 cu. ft. dryers, when viewed from the front of the unit, exhaust 3-way via rear, left and bottom. Dryer is shipped exhausted to the rear. Alternate exhausting knockouts are supplied.

Circuit requirements:

Electric: An individual, properly grounded branch circuit, protected by a 30-amp circuit breaker or a time-delay fuse is required.

Electric dryer rating:

240V, 5600W, 24A, 60Hz-5.8, 6.0 and 7.0 cu. ft. dryers 208V, 4400W, 22A, 60Hz-5.8, 6.0 and 7.0 cu. ft. dryers

Gas: An individual, properly grounded branch circuit, with a three-prong grounding-type receptacle, protected by a 15- or 20-amp circuit breaker or a time-delay fuse is required.

Gas dryer electric rating:

120V, 60Hz, 6A

Gas (BTU/HR): 22,000 for 5.8, 6.0 and 7.0 cu. ft. dryers. Factory-equipped for natural gas. Tested for LP gas. LP gas supply requires an optional conversion kit: 5.8, 6.0 and 7.0 cu. ft. model kit is WE25X0217. Have a qualified gas technician install a conversion kit. See dryer ducting information for proper installation.

Dryer note: Dryer wall outlet must be located within 36" of service cord entry and accessible when dryer is mounted in position.

As an ENERGY STAR® partner, GE has determined that the appliances marked with the ENERGY STAR logo meet the ENERGY STAR guidelines for energy efficiency.

Before purchasing an appliance, read important information about its estimated annual energy consumption or energy efficiency rating that is available from your retailer, ge.com or www.energystar.gov.

GE has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.

© 2006 GE Company Pub. no. 99-A016 PC44395

General Electric Company Louisville, KY 40225 ge.com