MONOGRAM 36" COMMERCIAL-STYLE FULLY INTEGRATED FRENCH-DOOR BOTTOM FREEZER



ZIP364NBVII





BOTTOM FREEZER WITH INTEGRATED INSTALLATION

Concealed hinge offers a look of seamless perfection that installs flush with surrounding cabinetry

6-TEMPERATURE SETTING CONVERTIBLE DRAWER

The convertible drawer with 6 temperature settings allows you to choose temperatures best suited for storing cold drinks, meat, snacks, ice cream, produce or frozen items

STATEMENT AND MINIMALIST COLLECTION REFRIGERATOR HANDLES (SOLD SEPARATELY)

Designed to enhance choice and customization, Statement and Minimalist Collection refrigerators do not come with handles, these must be chosen separately and ordered through a Monogram representative

PANEL-READY EXTERIOR WITH SIX-WAY ADJUSTABILITY

Statement and Minimalist Collection refrigerators accept stainless steel panels, which can be ordered separately from Monogram or your cabinetmaker

LED LIGHTING INSIDE REFRIGERATOR

Ramp-up LED interior lighting provides exceptional illumination throughout the fresh food compartment, accentuating the sophisticated interior and allowing you to easily see food in the refrigerator

WIFI-CONNECTED REFRIGERATOR

The WiFi refrigerator allows you to wirelessly control refrigerator settings from your smartphone, using an available app

ACCURATE, ELECTRONIC TOUCH CONTROLS

Upfront, electronic touch controls make it easy to adjust climate settings to create ideal food storage conditions

REFRIGERATOR WITH SOFT-CLOSE DRAWERS

The innovative sliding mechanism helps the drawers close gently and completely

HUMIDITY-CONTROLLED VEGETABLE AND FRUIT DRAWER

Enjoy additional storage flexibility settings that help to preserve food freshness

FACTORY-INSTALLED ICE MAKER

The water filtration system in the factory-installed ice maker supplies you with clean, fresh-tasting water and ice

SABBATH MODE REFRIGERATOR

This refrigerator with Sabbath mode is designed to disable functions in accordance with Sabbath-observing practices





Panels and handles are sold separately.

SPECIFICATIONS

Overall Width	35 3/4" (90.8)		
Overall Height	83 7/8" (213 cm)		
Overall Depth	24 3/4" (62.9 cm)		
Door Clearance	see TOP VIEW **Dim A		
Drawer Clearance*	21 9/16" (54.8 cm)		
Cutout Width	36" (91.4 cm)		
Cutout Height	84" (213.4 cm)		
Cutout Depth	25" (63.5 cm)		
Net Weight (approx)	550 lbs (250 kg)		

^{*}Note: Dimension is from front of 3/4" door panel to the handle on the middle drawer when the drawer is fully extended.


ATTENTION ELECTRICIAN:

A 115 volt 60Hz., 15 or 20 amp power supply is required. An individual properly grounded branch circuit or circuit breaker is recommended. For multiple unit installation, each unit requires separate individually properly grounded circuit or breaker and separate properly grounded 3-prong electrical receptacle recessed.

AWARNING:


When installing appliance, you must use and follow the product installation instructions. These can be found with unit or on web at monogram.com.

OVERALL DIMENSIONS



*Depth dimension without handle. Statement handle adds 2 9/16" depth. Minimalist handle adds 2 1/8" depth.

^{**}Includes 3/4" door panel





^{**}Dimensions based on Statement Handle height of 2 9/16" (6.5) and a hand clearance of 2" (5.1).

Dimensions in parentheses are in centimeters unless otherwise noted. Actual product dimensions may vary due to manufacturing tolerances.




SINGLE INSTALLATION





FLUSH 3/4" THICK PANEL DIMENSIONS SINGLE INSTALLATION



PANEL DIMENSIONS

Α	В	С	D	E
49 3/8"	17 13/16"	9 11/16"	20 9/16"	35 3/4"

INTEGRATED INSTALLATION

HELPFUL TIPS

- A minimum 6" (15.2) finished return matching cabinet exterior recommended on interior on all sides and top at front of opening
- Trimmed refrigerators are designed to be customized with decorative panels. Field-installed 3/4" custom door panels are required.
- Maximum total panel weight:
 Fresh Food Door 20.7 lbs.
 Convertible Drawer 7.6 lbs.
 Freezer Drawer 17.2 lbs.
 Note: For panels constructed with rails and stiles (5-panel), the rails that are a minimum of 3" wide and stiles that are a minimum of 4.5" wide.
- For Custom Panels: Use templates provided with units to pre-drill holes for mounting panel brackets (provided with unit). Adjustment screws and instructions also provided with units.
- Custom Panels require a custom handle from cabinetmaker or the ZKPN Handle Mounting Kit, which is required when using Statement or Minimalist handles (sold separately).
 Panel routing is required to use ZKPN kit; see ZKPN kit installation instructions for details.
- Stainless steel handle and panel options: ZK4SN360VSS: French-Door Stainless Steel door panel kit ZKSB4H4CVSS: Minimalist handle kit ZKSB4H4PVSS: Statement handle kit
- GE SmartConnect™ Refrigerator Tubing Kits: The only Monogram-approved plastic tubing is supplied inthe SmartConnect Plastic Tubing Kits WX08X10006: Water Line 8' (2.5m) WX08X 10015: Water Line 15' (4.6m) WX08X10025: Water Line 25' (7.6m)



When installing appliance, you must use and follow the product installation instructions. These can be found with unit or on web at monogram.com.