



# built-in cooking


2005 GE Profile™ and GE®  
built-in products common cutouts



*Profile*™

## 30" double and single wall ovens

Eleven models fit two cutouts.



JT980SKSS




JT915WFWW

	Double Wall Ovens	
	JT980	JT955
Oven capacity	4.3 Upper/ 4.4 Lower	4.1 Upper/ Lower
Trivection™ technology	Upper	
Speed baking	Upper	
Speed broiling	Upper	
Precise Air™ convection system	•	Upper
Multi-rack convection bake	•	Upper
Single-rack convection bake	•	Upper
Convection roast	•	Upper
Auto Recipe™ conversion	•	•
Self-clean oven	•	•
Light self-clean option	•	•
TrueTemp™ system	•	•
Broil element	6-Pass	6-Pass
Bake element	Dual upper/ 8-Pass lower	8-Pass
Electronic controls	Chef's guide™	Glass touch
Proof mode	•	Upper
Warm mode	•	Upper
Defrost mode	•	
Help mode	•	
Oven meat probe		Upper
Control lock capability	•	•
Certified Sabbath mode	•	•
CleanDesign oven/ hidden bake element		•
Big ClearView™ window	Big View	•
Oven light	2 Halogen	Halogen
Cookbook	Trivection	Convection

				Single Wall Ovens					
JT952	JTP50	JTP48	JTP28	JT930	JT915	JT912	JTP25	JTP20	
4.1 Upper/ Lower	4.4 Upper/ Lower	4.4 Upper/ Lower	4.4 Upper/ Lower	4.3	4.1	4.1	4.4	4.4	
				•					
				•					
				•					
Upper				•	•	•			
				•	•				
Upper				•	•	•			
Upper				•	•	•			
•				•	•	•			
•	•	•	Upper	•	•	•	•	•	
•				•	•	•			
•	•	•	•	•	•	•	•	•	
6-Pass	6-Pass	6-Pass	6-Pass	6-Pass	6-Pass	6-Pass	6-Pass	6-Pass	
8-Pass	8-Pass	8-Pass	8-Pass						
•	•	•	Upper	Chef's guide	Glass touch	•	•	•	
				•	•				
				•	•				
				•					
Upper					•	•			
•	•	•	Upper	•	•	•	•	•	
•	•	•	Upper	•	•	•	•	•	
•					•	•			
•	•	•	•	Big View	•	•	•	•	
•	•	•	•	2 Halogen	Halogen	•	•	•	
Convection				Trivection	Convection	Convection			

## 27" double and single wall ovens

Eight models fit two cutouts.



JK955BFBB




JKP20CFCC

	Double Wall Ovens	
	JK955	
Oven capacity (cu. ft.)	3.9 Upper/ Lower	
Precise Air™ convection system	Upper	
Multi-rack convection bake	Upper	
Single-rack convection bake	Upper	
Convection roast	Upper	
Auto Recipe™ conversion	Upper	
Self-clean oven	•	
Light self-clean option	•	
TrueTemp™ system	•	
Electronic controls	Glass touch	
Proof mode	Upper	
Warm mode	Upper	
Oven meat probe	Upper	
Control lock capability	•	
Certified Sabbath mode	•	
CleanDesign oven/ hidden bake element	•	
Big ClearView™ window(s)	•	
Oven light	Halogen	
Cookbook	Convection	

			Single Wall Ovens			
JKP50	JKP48	JKP28	JK915	JKP25	JKP20	JKS06
3.9 Upper/ Lower	3.9 Upper/ Lower	3.9 Upper/ Lower	3.9	3.9	3.9	3.9
			•			
			•			
			•			
			•			
•	•	Upper	•	•	•	
•	•		•	•	•	
•	•	•	•	•	•	•
•	•	•	Glass touch	•	•	•
			•			
			•			
			•			
•	•	•	•	•	•	•
•	•	•	•	•	•	•
			•			
•	•	•	•	•	•	•
•	•	•	Halogen	•	•	•
			Convection			

# 30" slide-in electric and gas ranges

Ten models fit one cutout.



JS998THWW




J2S968SHSS

	Trivection	
	JS998	
Self-clean oven w/Delay Clean option	•	
Trivection technology	•	
Precise Air™ convection system	•	
Convection bake	Single-/Multi-rack	
Convection roast	•	
Auto Recipe™ conversion	•	
TrueTemp™ system	•	
CleanDesign oven/hidden bake element		
Electronic controls	Chef's Guide™	
Proof mode	•	
Warm mode	•	
Dual 6"/9" ribbon heating element	1 (2500W)	
8" ribbon heating elements	1 (2000W)	
7" ribbon heating elements		
Bridge element		
6" ribbon heating element	2 (1500W)	
Warming zone (ribbon)		
Power Boil™ burner 15,000 BTU/180° simmer		
High Output burner (Nat.) 11,000 BTU/150° simmer		
Precise Simmer burner (Nat.) 6,000 BTU/140° simmer		
All-purpose burners (Nat.) 9,100 BTU/150° simmer		
Continuous grates		
Ignition system		
Certified Sabbath mode	•	
Interior oven light	2 Halogen	
Oven racks	3 Hvy-duty	

Electric					Dual-Fuel	Gas			
JS968	JSP47	JSP42	JSP39	JSS28	J2S968	JGS968	JGSP48	JGSP28	
•	•	•	•		•	•	•	•	
•					•				
Single-/ Multi-rack					Single-/ Multi-rack	•			
•					•	•			
•					•	•			
•	•	•	•	•	•	•	•	•	
•					•	•	•	•	
Glass touch	•	•	•	•	Glass touch	Glass touch	•	•	
•					•	•			
•					•	•			
1 (2500W)	1 (2500W)	1 (2500W)							
	1 (2000W)	1 (2000W)	2 Calrod	2 Calrod					
2 (1800W)									
1 (800W)									
1 (1500W)	2 (1500W)	2 (1500W)	2 Calrod	2 Calrod					
(120W)									
					1 Sealed	1 Sealed			
					(1) 11,000 BTU Sealed	(1) 11,000 BTU Sealed	(2) 11,000 BTU Sealed	(2) 12,000 BTU Sealed	
					1 Sealed	1 Sealed	1 Sealed		
					1 Sealed	1 Sealed	1 Sealed	2 Sealed	
					•	•	•	•	
					Electronic	Electronic	Electronic	Electronic	
•	•	•	•	•	•	•	•	•	
Halogen	•	•	•	•	Halogen	Halogen	•	•	
3 Hvy-duty	2	2	2	2	3 Hvy-duty	3 Hvy-duty	2 Hvy-duty	2	

## 36" electric and gas cooktops

Eleven models fit one cutout.



JP970SKSS



JGP975SEKSS


	Electric	
	JP980	JP970
Cooktop surface	Ceramic-glass	Ceramic-glass
12"/9"/6" tri-ring heating element		1 (3000W)
Dual 6"/9" ribbon heating element	1 (2500W)	
Dual 5"/8" ribbon heating element	1 (2200W)	1 (2200W)
7" ribbon heating elements	1 (1500W) w/warmer	1 (1500W)
Bridge element		
6" ribbon heating element	2 (1200W)	2 (1200W)
Hot surface indicator lights	5	5
Precise Digital Control System™	•	
8" heating elements		
6" heating elements		
Cooktop burners		
Power Boil™ burner		
15,000 BTU/180° simmer		
High Output burner (Nat.)		
Precise Simmer burner (Nat.)		
Electronic pilotless ignition		
Dual flame stacked burner		
18000 BTU/140° simmer		
Cooktop lockout	•	•
Die cast knobs (SS)		•



			Gas					
JP960	JP655	JP626	JGP975	JGP970	JGP963	JGP637	JGP630	JGP628
Ceramic-glass	Ceramic-glass	Porcelain-enameled	Stainless, Porcelain	Ceramic-glass	Stainless, Porcelain	Tempered glass	Stainless, Porcelain	Stainless, Porcelain
1 (2500W)	1 (2500W)							
2 (1800W)	1 (1500W)							
1 (800W)								
1 (1200W)	2 (1200W)							
5	5							
	1 (2000W)	2 Plug-in						
		2 Plug-in						
			5 Sealed	5 Sealed	5 Sealed	5 Sealed	5 Sealed	4 Sealed
				•	•			
			•	•	•	•	•	
			2	2	2	2	2	•
			•	•	•	•	•	•
			•					
•			•	•				
			•	•				

## 30" electric and gas cooktops

Thirteen models fit one cutout.



JP940SKSS




JGP940SEKSS

	Electric		
	JP950	JP940	JP930
Cooktop surface	Ceramic-glass	Ceramic-glass	Ceramic-glass
Dual 6 <sup>5</sup> / <sub>9</sub> " ribbon heating element	1 (2500W)	1 (2500W)	1 (2500W)
Dual 5 <sup>5</sup> / <sub>8</sub> " ribbon heating element	1 (2200W)	1 (1900W)	
8" ribbon heating elements	1 (2000W)	1 (2000W)	
7" ribbon heating elements			2 (1800W)
Bridge element			1 (800W)
6" ribbon heating elements	1 (1200W)	1 (1200W)	1 (1200W)
Hot surface indicator lights	4	4	4
Precise Digital Control System™	•		
8" heating elements			
6" heating elements			
Cooktop burners			
High Output burner (Nat.) 11,000 BTU/ 150° simmer			
Precise Simmer burner (Nat.) 6,000 BTU/ 140° simmer			
Electronic pilotless ignition			
Continuous grates			
Cooktop lockout	•	•	•
Die cast knobs (SS)		•	
Dual flame stacked burner 18000 BTU/ 140° simmer			
Power Boil burner 15000/ 180° simmer			

		Gas						
JP910/ JP355	JP340	JGP945	JGP940	JGP933	JGP337	JGP330	JGP328	JGP321
Ceramic-glass	Ceramic-glass	Stainless, Porcelain	Ceramic-glass	Stainless, Porcelain	Tempered glass	Stainless, Porcelain	Stainless, Porcelain	Porcelain-enameled
1 (2500W)								
2 (2000W)	2 (2000W)							
1 (1200W)	2 (1200W)							
4	1							
		4 Sealed	4 Sealed	4 Sealed	4 Sealed	4 Sealed	4 Sealed	4 Sealed
		.	.	.	.	.	.	
		.	.	.	.	.	.	
		.	.	.	.	.	.	.
		.	.	.	.	.	.	.
JP910 only		.	.					
		.	.					
		.						
			.	.				

# 30" electric and gas downdraft cooktops

Three models fit one cutout.



JP989BKBB



JGP989KKCC

	Electric		Gas
	JP989	JP389	JGP989
Configuration		Dual modular	
Cooktop surface	Ceramic-glass	Porcelain-enameled	Ceramic-glass
Downdraft exhaust	400 CFM	400 CFM	400 CFM
Three-speed downdraft vent fan	•	•	•
Infinite heat controls	•	Rotary	
Heating element "ON" indicator light	•	•	
Number of elements	4	Optional modules	
Dual 6 7/9" ribbon heating element	1 (2500W)		
7" ribbon heating elements	2 (1800W)		
Bridge element (ribbon)	1 (800W)		
6" ribbon heating elements	1 (1500W)		
Cooktop burners			4 Sealed
Electronic pilotless ignition			•
Burner grates			2



**GE Consumer & Industrial**  
Appliances  
General Electric Company  
Louisville, KY 40225  
ge.com