PDW7800/80R GE Profile™ Built-In Dishwasher

Dimensions and Installation Information (in inches)

Electrical Rating

Voltage AC	120
Hertz	60
Total connected load amperage	9.1
Calrod® heater watts max	875

For use on adequately wired 120-volt, 15-amp circuit having 2-wire service with a separate ground wire. This appliance must be grounded for safe operation.

22-1/2 27-1/2 33-13/16" MIN. adj. to 35" 21-1/4 Countertop This wall area 90° must be free of → pipes or wires 4 (Adjustable) 24" Electrical MIN. wiring is 3" from cabinet Hot water Electrical 34" to 34-3/4" Underside line on wiring on right left of countertop Plumbing and electrical service must enter inside shaded area 19" MIN. from wall 24" From wal 24" MIN.

25-1/4

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.







As an ENERGY STAR® partner, GE has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

PDW7800/80R GE Profile™ Built-In Dishwasher

Features and Benefits

- Self-cleaning 5-stage filtration The wash system's multiple filtration levels ensure clean dishes
- Steam pre-wash Loosens tough soils before any cycle virtually eliminating the need for soaking or pre-rinsing dishes
- Platinum silver nylon coated racks Durable racks secure dishes
- 2 utility shelves with StemSafe Multiple shelves create space and protect stemware
- 4 Cycles/5 Options Makes it easy to select from a wide range of wash cycles and options
- Up to 16 place setting capacity nylon racking Durable racking holds familysized dish loads
- Countdown display with 1–9-hour Delay Start Electronic display counts down to the pre-programmed start time
- Dedicated silverware jets Precisely dedicated spray jets target the silverware for optimal cleaning
- Model PDW7800RWW White on white
- Model PDW7800RCC Bisque on bisque
- Model PDW7800RBB Black on black
- Model PDW7880RSS Stainless steel (shown)





