

Hotpoint®

DUCTLESS HEAT PUMP

America's hardest working equipment.

Hotpoint® ductless mini-split systems deliver unmatched heating and cooling at an accessible price point. When pros choose Hotpoint® they're providing homeowners with best-in-class performance, nonstop comfort, and superior reliability — all backed by one of the toughest names in the industry.



ENVIRONMENTALLY COMPLIANT

All Hotpoint® systems use R-32 refrigerant, ensuring that they meet EPA Low GWP refrigerant regulations.*



WI-FI CONNECTIVITY

Hotpoint® systems connect seamlessly to the SmartHQ™ App from GE Appliances, giving homeowners more control over their comfort.



PROTECTIVE BASE PAN HEATER

A built-in base pan heater on outdoor units prevents systems from freezing, keeping systems operating at peak performance.



ALL-SEASON COMFORT

With heating down to -15°F and cooling up to 115°F, homeowners know they're coming home to comfort — no matter the weather outside.



EFFICIENT OPERATION

High-power turbo mode and warm start technology help heat and cool rooms more quickly, and an auto louver adjusts airflow upward when cooling and downward when heating.



HIGH-PERFORMANCE INVERTER TECHNOLOGY

A DC inverter compressor keeps indoor temperatures consistent in almost any climate and helps homeowners save money on energy.



FEDERAL & STATE INCENTIVES

Eligibility for federal and state incentives makes Hotpoint® the easy choice for price-conscious consumers.**



EASY TO INSTALL, EASY TO SERVICE

A mounting template and mounting plate with dimensions make installation a breeze, while an extended kickstand and easy-access control board let you service systems without removing casings. Plus, a two-way piping drain on the right and left sides makes installation easier and ensures units fit in more applications.



WORRY-FREE WARRANTY

Unlock a 5-year limited parts and compressor warranty with registration.



BUILT TO LAST

A hydrophilic aluminum fin helps prevent condensation buildup and ensures water flows through the unit smoothly.



AIR & WATER
SOLUTIONS

DUCTLESS HEAT PUMP

MODEL SPECIFICATIONS



		09K	12K	18K	24K
Model Number	Outdoor	1H09HN2DAA	1H12HN2DAA	1H18HN2DAA	1H24HN2DAA
	UPC	084691944430	084691949473	084691949497	084691949510
	Indoor	HW09HN2DAA	HW12HN2DAA	HW18HN2DAA	HW24HN2DAA
	UPC	084691949466	084691949480	084691949503	084691949527
Cooling	Capacity Range Btu/hr	3,100-10,000	3,300-13,800	4,100-20,000	4,700-25,200
	SEER2	18	18	18	18
	EER2	12	12	12	10.6
	Rated Capacity 95°F Btu/hr	9,000	12,000	18,000	24,000
	Moisture Removal Pt./h	1.0	1.2	2.2	2.4
Heating	Heating Capacity Range Btu/hr	2,100-11,000	2,800-13,300	3,800-20,000	4,300-25,600
	HSPF2 (IV)	9.5	9.5	9.5	9.5
	HSPF2 (V)	7.2	7.1	7.2	7.1
	Rated Heating Capacity 47°F Btu/hr	10,000	13,000	19,000	25,000
	Rated Heating Capacity 5°F Btu/hr	7,000	9,100	13,300	17,500
	Max. Heating Capacity 5°F Btu/hr	7,000	9,100	13,300	17,500
Operating Range	COP@5F	1.8	1.8	1.8	1.8
	Heating °F(°C)	14-115(-10-46)	14-115(-10-46)	14-115(-10-46)	14-115(-10-46)
Power Supply	Cooling °F(°C)	-15-75(-26-24)	-15-75(-26-24)	-15-75(-26-24)	-15-75(-26-24)
	Voltage, Cycle, Phase V/Hz/-	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1
Outdoor Unit	Compressor Type	DC Inverter Driven Rotary	DC Inverter Driven Rotary	DC Inverter Driven Rotary	DC Inverter Driven Rotary
	Maximum Fuse Size A	15	15	20	25
	Minimum Circuit Amp A	12	12	14	18
	Base Pan Heater	Yes	Yes	Yes	Yes
	Outdoor Noise Level dB	55	55	59	60
	Dimension: Height in (mm)	21 3/4 (553)	21 3/4 (553)	25 1/4 (642)	25 1/4 (642)
	Dimension: Width in (mm)	31 1/2 (800)	31 1/2 (800)	32 1/4 (820)	32 1/4 (820)
	Dimension: Depth in (mm)	11 (280)	11 (280)	12 (306)	12 (306)
Indoor Unit	Weight (Ship/Net)- lbs (kg)	80.47/67.9 (36.5/30.8)	80.47/67.9 (36.5/30.8)	93.26/80.69 (42.3/36.6)	96.34/83.78 (43.7/38)
	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
	Maximum Indoor Sound Level (dB) (Turbo/High/Med/Low/Quiet)	45/43/38/32/28	46/44/39/33/29	49/46/43/40/31	54/50/47/44/38
	Dimension: Height in (mm)	11 (292)	11 (292)	12 1/8 (307)	13 5/8 (345)
	Dimension: Width in (mm)	31 3/4 (805)	31 3/4 (805)	34 1/2 (875)	43 1/2 (1105)
	Dimension: Depth in (mm)	7 7/8 (200)	7 7/8 (200)	8 1/2 (217)	9 1/2 (240)
	Weight (Ship/Net)- lbs (kg)	24.47/18.74(11.1/8.5)	24.47/18.74 (11.1/8.5)	28.22/21.83 (12.8/9.9)	41.67/32.63 (18.9/14.8)
	Refrigerant	R32	R32	R32	R32
	Connections	Flare	Flare	Flare	Flare
	Refrigerant Line	Liquid O.D. in	1/4	1/4	1/4
Suction O.D. in		3/8	3/8	1/2	1/2
Factory Charge Oz		25.8	25.8	38.8	46
Maximum Line Length (Ft)		66	66	83	83
Line Length no additional charge needed (Ft)		25	25	25	25
Maximum Height (Ft)		33	33	50	50

*Hotpoint models use R32 refrigerant. R32 is classified as a mildly flammable A2L refrigerant. At this time, some building codes restrict the use of products with A2L refrigerants in some applications. These restrictions vary by location. Refer to all local building codes for guidance on acceptable use of Low GWP (A2L) refrigerants for your application.

**All Hotpoint heat pumps are certified CEE Tier-2 except 24K units installed in the South region. Products certified to CEE Tier-2 are eligible for federal tax credits and Energy Star certified models are eligible for IRA rebates. See CEE directory for qualifying models: <https://www.ahrinet.org/cee-directory>.

