MONOGRAM 30" BUILT-IN DOUBLE OVEN

ZTD90DPSNSS











THE MONOGRAM STATEMENT COLLECTION

Edge-to-edge handles, polished stainless steel, and hand-finished edges convey a sense of solidity and beauty

LCD CONTROLS

Allow you to adjust oven settings with little effort

WIFI CONNECT

Perfectly in sync with a busy lifestyle, Alexa or Google Home can be used to control an array of oven functions from both inside and outside the home

PRECISION COOKING MODES

Master new recipes and perfectly execute favorite dishes using this ultra-smart system that automatically tracks cooking progress, modifies temperatures and adjusts cook times

NO-PREHEAT AIR FRY

A must-have for health-conscious cooks, the No-Preheat Air Fry mode crisps food to crunchy perfection, without using oils or butter

SCAN-TO-COOK

Innovative and time saving, scan-to-cook technology ensures that packaged foods are always prepared correctly. A simple scan of the barcode with a smartphone delivers consistently, delicious results

TRUE EUROPEAN CONVECTION WITH DIRECT AIR

Channels heated air from the top of the oven and circulates it around food on all sides for perfectly uniform baking and roasting

10.0 CUBIC FOOT OVEN CAPACITY (5.0 EACH OVEN)

Easily accommodates even the largest meals

EXCLUSIVE SELF-CLEAN (2 FULL-EXTENSION, 4 REGULAR) OVEN RACKS

Glide in and out smoothly on stainless steel ball bearings, and are designed to be left in the oven during the self-clean cycle

TEN-PASS BAKE ELEMENT

Covers more surface area for more even baking results

SOFT-CLOSE DOORS

An expertly engineered hinge ensures that the oven door closes quietly and smoothly, every time

EIGHT-PASS BROIL ELEMENT

Provides complete coverage and even browning, even for large dishes

SELF-CLEAN WITH STEAM CLEAN OPTION

Gives you flexible options for thorough oven cleaning



WALL INSTALLATION **TOP VIEW** 2 1/2" 1 7/16 (6.4) Side clea depth 30" (76.2) flush inset width with 1/8" (0.3) reveals 24 15/16" (63.3) min cutout depth 1 1/8" (2.8) Top cleat Α 5 1/4" ELEC. top cleat -side cleat 51 7/16" (130.6) Flush inset height with 1/8" (0.3) reveal at top and bottom (1.9) Side cleats 28 1/2" (72.4) cutout width 30" (76.2) 9/16" (1.4) Bottom cleat (Extends full depth of cabinet) bottom cleat **FLUSH INSET** FLUSH INSET INSTALLATION **INSTALLATION** FRONT VIEW

Allow 1/8" (0.3 cm) clearances from side edges of oven door.

HELPFUL TIPS

- A Junction box location (May also be located in adjacent cabinet.)
- B Platform must be able to support 400 lbs (181 kg)
- Cabinet surfaces must be an appearance finished surface for flush installation.
- Cleats may be visible and should be finished to match cabinetry.
- E If using optional flush install vent trim accessory ZX30VT2, please adjust cutout height to 51-1/8" and bottom cleat height to 1/4".

For more details, refer to the installation instructions for this product on Monogram.com. Dimensions in parentheses are in centimeters unless otherwise noted.