ZDBT240PBS

GE Monogram Beverage Center with Liquid Crystal Privacy Glass

Dimensions and Installation Information Installation Space

The Monogram® Beverage Center may be installed beneath a countertop or can be used free-standing.

• If installing between frameless cabinets, a 1/2"-wide filler strip or side panel may be required. The filler strip will act as a spacer between the door case and adjacent cabinet and will prevent interference with cabinet door swing. The width of the opening must include filler panels.

Note: When installed, the door should project forward 1" of adjacent 24"-deep cabinets.

Location Requirements

All Monogram Refrigeration Modules may be closed in on the top and sides as long as the front is unobstructed for air circulation and door swing.

- Do not install these products where the temperatures will go below 55°F (13°C) or above 90°F (32°C).
- Do not install where they will be subject to direct sunlight, heat or moisture.
- These products are not designed to be stacked one over the other.

Side-by-Side Installation

For a complete refreshment center, install a Monogram Wine Reserve and Beverage Center together.

- Products must operate from separate properly grounded receptacles.
- Do not install where they will be subject to direct sunlight, heat or moisture.


Door Swing Clearances

All Monogram Refrigeration Modules are factory set for a 110° door swing. When installed in a corner:


- Allow the minimum door swing clearances shown.
- The minimum clearance shown at 90° will allow full extension of drawers and shelves.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.





Dimensions and installation instructions are shown in inches.



Electrical

A 120V, 60Hz, 15 or 20 amp power supply is required. An individual properly grounded branch circuit or circuit breaker is recommended. Install a properly grounded 3-prong electrical recessed into the back wall as shown. Electrical must be located on rear wall as shown. **Note**: GFCI (ground fault circuit interrupter) is not recommended.



ZDBT240PBS

GE Monogram Beverage Center with Liquid Crystal Privacy Glass

Grounding the Beverage Center

IMPORTANT — (Please read carefully)

FOR PERSONAL SAFETY, THIS APPLIANCE MUST BE PROPERLY GROUNDED.

The power cord of this appliance is equipped with a 3-prong (grounding) plug which mates with a standard 3-prong (grounding) wall receptacle to minimize the possibility of electric shock hazard from this appliance.

Have the wall outlet and circuit checked by a qualified electrician to make sure the outlet is properly grounded.

When a standard 2-prong wall outlet is encountered, it is your personal responsibility and obligation to have it replaced with a properly grounded 3-prong wall out.

DO NOT, UNDER ANY CIRCUMSTANCES, CUT OR REMOVE THE THIRD (GROUND) PRONG FROM THE POWER CORD.

DO NOT USE AN ADAPTER PLUG TO CONNECT THE REFRIGERATOR TO A 2-PRONG OUTLET.



DO NOT USE AN EXTENSION CORD WITH THIS APPLIANCE.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.



ZDBT240PBS

GE Monogram Beverage Center with Liquid Crystal Privacy Glass

Features and Benefits

- Privacy Glass Innovative liquid-crystal technology allows you to turn glass from opaque to clear with a simple press of the button. Opaque setting conceals contents from view
- Temperature Control Maintains a consistent temperature
- LED Temperature Display Allows you to monitor the temperature at a glance
- Beverage Shelf on Full-Extension Slides Holds up to five wine bottles or ten 12-oz. cans
- Unfinished Heart-Of-Cherry Wood Shelf Fronts – Can be finished to complement surrounding cabinetry
- Removable Spillproof Glass Shelves Help contain spills for ease of cleaning
- QuickSpace[™] Shelf Quickly slides out of the way to make room for tall items
- Soft Interior Lighting Automatically illuminates when the door is open, but can be activated by an on/off switch on the handle
- Glass becomes clear and light comes on by touching the on/off switch. The light stays illuminated for one hour or until you turn it off
- Stainless Steel Tubular Handle Designed to coordinate with other Monogram appliances
- Includes stainless steel and black toekicks
- Model ZDBT240PBS Stainless steel

