www.HaierAmerica.com






TABLE OF CONTENTS

SAFETY INFORMATION

product.

Remember to record the model and serial numbers. They are located on a

label on the ice maker.

Important Safety Instructions3
SET UP & USE
Supplies Required for Installation4
Parts Included4
Tools Required for installation 5
Installation Instructions5-7
Water Valve/Tubing Installation
Water Supply Connection9-10
Ice Maker Operation10
Tips and Care
TROUBLESHOOTING & WARRANTY
Ice Maker Fill Adjustment11
Customer Service11
Troubleshooting
Limited Warranty
PRODUCT REGISTRATION
Thank you for purchasing our Haier product. This easy-to-use manual will quide you in getting the best use of your Model Number

Staple your receipt to your manual. You will need it to obtain warranty service.

Date of Purchase

IMPORTANT SAFETY INSTRUCTIONS



TO AVOID ELECTRICAL SHOCK, WHICH CAN CAUSE DEATH OR SEVERE PERSONAL INJURY, DISCONNECT THE POWER SUPPLY BEFORE CONNECTING A WATER SUPPLY LINE TO THE REFRIGERATOR.

/!\ WARNING

DO NOT PLACE FINGERS OR HAND ON THE AUTOMATIC ICE MAKING MECHANISM WHILE THE REFRIGERATOR IS PLUGGED IN. THIS WILL HELP PROTECT YOU FROM POSSIBLE INJURY AS WELL AS PREVENT INTERFERENCE WITH MOVING PARTS OF THE EJECTOR MECHANISM AND THE HEATING ELEMENT THAT RELEASES THE CUBES.

PROFESSIONAL INSTALLATION IS RECOMMENDED.

TO AVOID PROPERTY DAMAGE:

- Copper tubing is recommended for the water supply line. Water supply tubing should be 1/4". Plastic is not recommended since it greatly increases the potential for water leaks.
- Do not install water supply tubing in areas where the temperature falls below freezing.
- Connect the ice maker to a drinkable water source that is not connected to a water softening system. Chemicals from the softener may damage the ice maker, causing it to malfunction.


SAVE THESE INSTRUCTIONS HOUSEHOLD USE ONLY


SUPPLIES REQUIRED FOR INSTALLATION

The following items are required to install the ice maker.

- 1/4-inch copper supply line with shut off valve.
- ¼-inch brass compression nut and ferrule (sleeve).

NOTE: The copper tubing and shut off valve should be available at your local hardware or plumbing supply store. Coil enough tubing in the back of the unit to allow movement of the refrigerator for cleaning.





PARTS INCLUDED









Ice Bucket

Water Valve

Grommet








Water Tube Clamp



Water Tube Clip Qty: 2



Hose Clamp



Fill Tube



#8 Screw Qty: 5



Installation Checklist



User Manual

PAGE 4 • SET UP & USE

LIMITED WARRANTY

In-Home Service - What is covered and for how long?

This warranty covers all defects in workmanship or materials of the automatic ice maker for a period of:

12 months labor

12 months parts

The warranty commences on the date the item was purchased and the original purchase receipt must be presented to the authorized service center before warranty repairs are rendered.

What is covered?

1. The mechanical and electrical parts, which serve as a functional, purpose of this kit for a period of 12 months.

What will be done?

- 1. We will repair or replace, at our discretion any mechanical or electrical part which proves to be defective in normal usage during the warranty period so specified.
- 2. There will be no charge to the purchaser for parts and labor on any covered items during the initial 12 month period.
- 3. Contact your nearest authorized service center. For the name of the nearest service center please call 1-877-337-3639

THIS WARRANTY COVERS WITHIN THE CONTINENTAL UNITED STATES. PUERTO RICO AND CANADA. IT DOES NOT COVER THE FOLLOWING:

- Damages from improper installation.
- Damages occurred during shipping.
- Damage from end user's misuse, abuse, accident, alteration, lack of proper care and maintenance or incorrect current or voltage.
- Damage from non-household use.
- Damage from service by other than an authorized dealer or service center.
- Improper installation. If you have an installation problem, contact your dealer or installer. You will be responsible for providing adequate electrical, plumbing and other connecting facilities, including the water line to the ice maker and the water line installation.
- Replacement of house fuses or resetting of circuit breakers.
- Failure of the product if it is used for other than its intended purpose or used commercially.
- Damage to product caused by inevitable accidents, natural disasters such as fire, floods or other Acts of God.

WARRANTOR IS NOT RESPONSIBLE FOR CONSEQUENTIAL DAMAGES. THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy provided in this warranty is exclusive and is granted in lieu of all other remedies. This warranty does not cover incidental or consequential damages, so the above limitations may not apply to you. Some States do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary, from state to state.

Haier America

New York, NY 10018

TROUBLESHOOTING


PROBLEM	CAUSE/SOLUTION
No ice produced	Ensure that refrigerator is plugged in to power source
	Wire control arm is fully raised. See Page 10.
	Check that ice maker is plugged into electrical socket in rear of freezer compartment. See Pages 5-6.
	Water supply is turned off or disconnected.
	Disconnect refrigerator from power source, remove rear access cover, then check to see that water valve is plugged into wiring harness in rear bottom compartment.
	Check water connections on water valve. See Page 8.
Low/slow ice production	Adjust freezer temperature to colder setting. See Refrigerator User Manual for instructions.
	Check for leaks or kinks in water tubing on rear of refrigerator.
Water leak in freezer	Check that fill tube is aligned into fill cup on rear of ice maker. See Page7.
Water leak under refrigerator	Check for leaks in water tubing on rear of refrigerator.
	Disconnect refrigerator for power supply, remove rear compartment cover, then check water connections on water valve.

TOOLS REQUIRED FOR INSTALLATION


- 1/4-inch socket wrench or nut driver
- Phillips & Flathead screwdriver
- Wire Cutters
- Adjustable wrench
- Pliers


INSTALLATION INSTRUCTIONS

- 1. Move refrigerator away from wall and unplug.
- 2. Remove freezer shelf by lifting up and sliding it out of freezer compartment.




- 3. Remove electrical socket cover by gently prying the top snap loose with a flathead screwdriver. Be careful not to scratch the rear compartment cover.
- 4. Remove plastic plug above electrical socket using a flat-head screwdriver to gently pry plug away from rear cover.






5. Remove waterway label and compressor cover from rear of refrigerator.




INSTALLATION INSTRUCTIONS CONT.


6. Insert water fill tube fully into grommet.




7. Insert water supply tube fully into grommet. Use pliers to pinch open tabs on hose clamp and slide over bottom of grommet to secure supply line.




 Insert fill tube into hole until flange is tight against back of the cabinet.
 Rotate grommet back and forth to help with installation. Water supply tube to point straight down.




9. Install two #8 screws half way into screw mounting holes provided on left wall of freezer compartment.



10. Position ice maker harness in ice maker hook as shown below:



11. Insert ice maker electrical plug into socket on rear wall of freezer.




ICE MAKER FILL ADJUSTMENT


THESE INSTRUCTIONS SHOULD ONLY BE USED IF THE HOME HAS UNUSUALLY LOW WATER PRESSURE THAT RESULTS IN LOW ICE PRODUCTION OR SMALL ICE CUBE SIZE. CHANGES TO HOME PLUMBING COULD AFFECT ICE MAKER FILL AMOUNT AND RESULT IN OVERFLOWED WATER IN THE FREEZER COMPARTMENT.


If your ice maker is making small ice cubes or isn't producing a satisfactory amount of ice, it is possible to improve this by adjusting the amount of water used to fill the ice cube tray in the ice maker.

NOTE: Increasing the water fill amount could cause water to overflow the ice maker. Make half-turn adjustments until ice cube size or ice production amount is satisfactory. Allow 24 hours between adjustments. Closely monitor the freezer compartment for water overflow after fill adjustment.

 Use flathead screwdriver to pry front cover of ice maker. Do not discard front cover.







3. Replace front cover of ice maker.

NORMAL OPERATING SOUNDS

The following sounds are normal when the ice maker is operating:

- Motor running (inside freezer compartment)
- Ice dropping into ice bucket (inside freezer compartment)
- Running water (inside freezer compartment)
- Water valve opening or closing (clicking from back of refrigerator)

CUSTOMER SERVICE

IMPORTANT

DO NOT RETURN THIS PRODUCT TO THE STORE

If you have a problem with this product, please contact the Haier Customer Satisfaction Center at 1-877-337-3639

DATED PROOF OF PURCHASE, MODEL NUMBER AND SERIAL NUMBER REQUIRED FOR WARRANTY SERVICE




P/N 0060519192 Rev A

PAGE 6 ● SET UP & USE

PAGE 11 ● SET UP & USE

WATER SUPPLY CONNECTION CONT.

- 7. Reconnect refrigerator to power supply.
- 8. Turn icemaker ON by lowering wire control arm.



ICE MAKER OPERATION

NOTE: It takes approximately 24 hours for the ice maker to produce ice. New plumbing may cause ice discoloration and poor flavor. Discard ice made in the first 24 hours.

To stop the ice maker, lift the wire arm until it clicks and locks in the OFF (raised) position. The ice maker turns OFF automatically when the ice container is full.

TIPS AND CARE


- Water quality determines ice quality. Do not connect the ice maker to water that is softened. Chemicals from a malfunctioning softener can damage the ice maker.
- Ice stored too long may develop an odd flavor. Empty the container and make sure the wire arm is in the ON (lowered) position. The ice maker will then produce ice.
- Keep the wire arm in OFF position until the refrigerator is connected to the water supply or whenever the water supply is turned OFF.


CAUTION:

- Do not wash the ice container in your dishwasher.
- Be sure to stop the ice maker when cleaning the freezer or on vacation.
- If the ice maker has to be turned OFF for a long period of time, turn the water supply valve to the closed position.


INSTALLATION INSTRUCTIONS CONT.

- 12. Position fill tube into slot in rear of ice 13. Hangice maker from #8 screws maker fill cup.
 - then tighten screws.







14. Re-install freezer shelf on lowest rail and place ice bucket under the ice maker. Raise wire control off arm on the ice maker to OFF position.



WATER VALVE/TUBING INSTALLATION

1. Cut cable tie to access water valve electrical connector on right side of rear compressor compartment.







PAGE 10 . SET UP & USE PAGE 7 • SET UP & USE P/N 0060519192 Rev A


WATER VALVE/TUBING INSTALLATION CONT.

- 2. Remove rubber cap from water valve inlet.
- 3. Insert plastic water tube into bottom of water valve.






4. Attach water valve electrical connector to water valve.




 Insert supply line fully into valve inlet.
 Slide ferrule (sleeve) into valve inlet and tighten compression nut onto valve with wrench.


Do not over-tighten.



6. Attach water valve to right side of refrigerator using two #8 screws.



 Ensure wires are tucked behind water valve, away from condenser fan blades.



WATER SUPPLY CONNECTION




THIS WATER SUPPLY INSTALLATION IS NOT COVERED UNDER WARRANTY BY THE REFRIGERATOR OR ICE MAKER MANUFACTURER(S). FOLLOW THESE INSTRUCTIONS CAREFULLY TO MINIMIZE THE RISK OF EXPENSIVE WATER DAMAGE.

Supplies Required for Installation:

- Access to a household cold water line with water pressure between 20 psi and 120psi
- A water supply line made of 1/4-inch Outside Diameter, copper tubing. To determine the length of the copper tubing needed, you will need to measure the distance from the ice maker water valve at the back of the refrigerator to your cold water pipe. Then add approximately 7 feet, so the refrigerator can be moved out for service.
- A **shutoff valve** to connect the water supply line to your household water system **NOTE:** Do not use a self-piercing type shutoff valve.
- A compression nut and ferrule (sleeve) for connecting the water supply line to the ice maker inlet valve.
- 1. Turn off water supply at shut off valve.
- 2. Connect copper water supply line to household water system.
- 3. Turn ON water supply and tighten any connections that leak.
- 4. Re-install Rear Access Cover for compressor compartment.
- 5. Coil excess water supply line behind refrigerator, as shown below and arrange coils so they do not vibrate or wear against other surfaces. Use water tube clamp and #8 screw to secure water supply line to rear of refrigerator.



Place water tube clips on refrigerator back by peeling off liner and secure water tube to back of refrigerator.



PAGE 9 • SET UP & USE